T D	т п		0	□	A]
₽	ØS					4
	Keying Shown as example		LAYOUT SHOWN AS EX.	AMPLE		3
 CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III -Shell Material : Composite -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum 	Connector dimensionDimNominalØS38.5 MaxZ'31.5 MaxVV THREADM28x1-6g	im Nominal ØS 38.5 Max Z' 31.5 Max SOURIAU shall not be liable for any non-conformity or damage				2
 -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +175°C -Salt Spray : 2000 hours 		A 18-10-2016 ISS DATE Designed By:	PN: 8D519J2 First Release Latest modification - by Date:	11HA CUSTOMER DRAW	MOD N°	_
		TITLE				_
BASIC SERIES: 8D 5 - 19 SHELL TYPE : Plug with RFI Shielding	J 11 H A ORIEN CONTACT TYPE : PIN (150	TATION : A SOURIAU	Tolerances:	859 This document is	the property of IIAU reproduced or	_ 1
PLATING : J = Olive drab Cadmium		DUT : 19-11 FORMAT A3	SOURIAU 8D519J1		SHEET 1/2	_

