			0	د	>	
Z						
			LAYOUT SHOWN AS EX			
	Keying Shown as example					
CHARACTERISTICS	Connector dimension Dim Nominal	-				
-Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy	ØS 41.7 Max Z 31 Max VV THREAD M31x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer			Country			
 -Contact Plating : Gold over copper Alloy 0.8µm minimum -Durability : 500 Mating cycles -Delivered without Souriau contacts 		FR Not Listed PN: 8D521F41SDL				
-Temperature Range - 65°C to +200°C		A 06-10-2	016 First Release			
-Salt Spray : 48 hours					MOD N°	
Mass : 43.78 g ± 10%		ISS DATE Designed By:	Date:	CUSTOMER DRAWING		
	TITLE Aluminium Plug 8D s					
BASIC SERIES: 8D 5 - 21 F	41 S D L	V/O Contacts NA	General linear Tolerances:	NPRDS / PROJECT 859		
CONTACT TYPE : Standard Crimp Contact			- SOURIAU WWW.SOURIAU.COM This document is the SOURIAU it must not be repro			
SHELL SIZE : 21	CONTACT TYPE : SOCKET(5			communicated without	communicated without permission	
PLATING : F = Nickel	CONTACT LAY	OUT : 21-41 FORMAT A3	SOURIAU 8D521F4		SHEET	

	т	പ	п –	m		<u>о</u>	
		Contact Layout					
4		+Y 7 HOLES					
	<	31 23 37 41					
		A Contraction of the second se					
		635 DIA					
ယ	Shell Arrangement Numt size no. cont	tacts contacts rating location					
~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	21 -41 4	I1 20 I All MS20055-41					
	4						
$\sim$	_					SOURIAU shall not be liable fo	or ar
						due to a use of the Product	ts w
						the Specifications issued by eith (professional recomme	
N							ount FR
						PN: 8D52	)16
						111.0052	
					A 06-10-20	16 First Release	
					ISS DATE		
					Designed By:	Date:	
					TITLE	Alur	mir
					SCALE	General line	ear
					NA	Tolerances	
					SOURIA	U WWW.SOURIAU	J.(
					FORMAT	SOURI	ΔΙ
					A3	8D521	LF4
	Н	G	F	E	7 D	C	
					V		

