ت <u>م</u> <u>ت</u>	m		0	₿ >		
			LAYOUT SHOWN AS EXA	AMPLE		
Keying Shou						
CHARACTERISTICS	in as example					
-Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal					
-Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)					
-Seals & Grommet : Silicon Elastomer			Country FR	Jurisdiction & Control List Not Listed		
 Contact Plating : Gold over copper Alloy 0.8μm minimum Durability : 500 Mating cycles Delivered with Souriau contacts and Accessories 			PN: 8D521F4			
-Temperature Range : -65°C to +200°C		A 06-10-2016	First Release			
-Salt Spray : 48 hours		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	<u> </u>
	TITLE Aluminium Plug 8D series					
→ BASIC SERIES: 8D 5 - 21 F 42 B B SHELL TYPE : Plug with RFI Shielding		SCALE -{	General linear Tolerances:	NPRDS / PROJECT 859		_
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 21	ORIENTATION : B CONTACT TYPE : SOCKET(500 Matings)	SOURIAU		This document is the p SOURIAU it must not be reproc communicated without	luced or	
PLATING : F = Nickel	CONTACT LAYOUT : 21-42	FORMAT	SOURIAU I		SHEET	_
		A3	8D521F42		1/2	
H G F	Ε	D	С	ВАА		_

	Ŧ	G	г	m	D	0	
4		Contact Layout 42					
	Ctc A B	2#4 Power 21-42 X Y 0 6.19 0 -6.19					
ω							
	F					SOURIAU shall not be liabl due to a use of the Pro the Specifications issued by (professional recom	oducts wh either o mmendat
N						PN: 8D	Countr FR
					ISS DATE Designed By:	16 First Release Latest modification - by Date:	
_ _					SCALE NA		
					FORMAT A3	SOUI	RIAU
	Н	G	F	E	D AS	C 8D5	521F4

