	т (•	∞ >		
A Z ØS-						
			LAYOUT SHOWN AS EXA	MPLE		
	Keying Shown as example					
CHARACTERISTICS	Connector dimension Dim Nominal	7				
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer	ØS 41.7 Max Z 31 Max VV THREAD M31x1-6g		SOURIAU shall not be liable for any r due to a use of the Products whic the Specifications issued by either of th (professional recommendatio	h does not comply with ne Parties or by a third party n, technical notice.)		
 Sincon Eastorner Sold over copper Alloy 0.8µm minimum 			Country FR	Jurisdiction & Control List Not Listed		
-Durability : 500 Mating cycles -Delivered without Souriau contacts			PN: 8D521F4	2SAL		
-Temperature Range : -65°C to +200°C -Salt Spray : 48 hours		A 06-10-20	016 First Release			
		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	
		TITLE	Aluminiu	ım Plug 8D series	es	
BASIC SERIES: 8D 5 - 21 F SHELL TYPE : Plug with RFI Shielding	42 S A L Delivered V	SCALE //O Contacts NA	General linear Tolerances:	NPRDS / PROJECT 859		
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 21			U WWW.SOURIAU.CC	This document is the pro- SOURIAU it must not be reproduced communicated without p	uced or	
			SOURIAU		SHEET	
PLATING : F = Nickel	CONTACT LA	YOUT : 21-42	SUUKIAU L	JKG N	SHEET	

	тт	െ	н Г	m	D	0	
4	(Contact Layout 42					
	Ctc A B	2#4 Power 21-42 X Y 0 6.19 0 -6.19					
ω							
	 -					SOURIAU shall not be liab due to a use of the Pro the Specifications issued by (professional recor	oducts wh y either o mmendat
N						PN: 8D	Countr FR 0521F
					A 06-10-202 ISS DATE Designed By:	16 First Release Latest modification - by Date:	
<u> </u>					SCALE NA		Alumin al linear rances: ±
					FORMAT A3	SOU	
l	Н	G	F	E	D	C	

