т Q т т			0	₽		•
			LAYOUT SHOWN	AS EXAMPLE		
Kaning Shawa as avample						
CHARACTERISTICS	-					
-Standard : Based on MIL-DTL-38999 Series III Dim Nominal	-					
-Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
-Seals & Grommet : Silicon Elastomer					tion & Control List	
-Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles -Delivered without Souriau contacts			PN: 8D52	I	Not Listed	
-Temperature Range : -65°C to +200°C		06-10-2016 Eirst Pol	0250			
-Salt Spray : 48 hours		A 06-10-2016 First Release ISS DATE Latest modification - by		MOD N°		
	Designer		Date:		CUSTOMER DRAWING	
	1	TITLE Aluminium Plug 8D series			series	
BASIC SERIES: 8D 5 - 21 F 42 S D L	SCAL		General line Tolerances		NPRDS / PROJECT	
SHELL TYPE : Plug with RFI Shielding Delivered W	I/O Contacts NA		±		859 This document is the p	roperty of
CONTACT TYPE : Standard Crimp Contact ORIE SHELL SIZE : 21 CONTACT TYPE : SOCKET(5)		N:D SOURIAU WWW.SOURIAU.COM SOURIAU it must not be reproduced		luced or		
PLATING : F = Nickel CONTACT LAY		IAT TAI	SOURI	AU DRG N°		SHEET
	A	3		F42SDL-C		1/2
						1

r	т	۵	ار (m	D	0	
4	(Contact Layout 42					
	Ctc A B	2#4 Power 21-42 X Y 0 6.19 0 -6.19					
ω							
						SOURIAU shall not be liab due to a use of the Pro the Specifications issued by (professional recon	oducts wh v either o mmendat
N						PN: 8D	Countr FR 0521F
					A 06-10-202 ISS DATE Designed By:	16 First Release Latest modification - by Date:	
_ _					SCALE NA	Genera 	Alumin al linear ances: t
					FORMAT A3	SOU	
l	Н	G	F	E	D	C	•

