т (О)		0			
		LAYOUT S	HOWN AS EXAMPLE		
Keying Shown as example					
-Standard : Based on MIL-DTL-38999 Series III Dim No.	inal				
-Shell Material : Aluminium Z 31	Max Max (1-6g	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer				ction & Control List	
-Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles -Delivered without Souriau contacts		PN: 8	D521F42SEL	Not Listed	
-Temperature Range : -65°C to +200°C	A 06	-10-2016 First Release			
-Salt Spray : 48 hours					MOD N°
	Designed B			CUSTOMER DRAWING	
	пт	TITLE Aluminium Plug 8D series) series	
BASIC SERIES: 8D 5 - 21 F 42 S E L SHELL TYPE : Plug with RFI Shielding	SCALE NA		eral linear lerances: ±	NPRDS / PROJECT 859	
CONTACT TYPE : Standard Crimp Contact		RIAU WWW.SOL	IRIAU.COM	This document is the prop SOURIAU it must not be reproduce communicated without per	ed or
	ACT LAYOUT : 21-42	 	URIAU DRG N°		SHEET
	A3		0521F42SEL-C		1/2
	D	C	В		

r	т	۵	ار (m	D	0	
4	(Contact Layout 42					
	Ctc A B	2#4 Power 21-42 X Y 0 6.19 0 -6.19					
ω							
	+					SOURIAU shall not be liab due to a use of the Pro the Specifications issued by (professional recon	oducts wh either o mmendat
N						PN: 8D	Countr FR 0521F
					A 06-10-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:	
<u> </u>					SCALE NA	Genera Tolera	Alumin al linear ances:
					FORMAT A3	SOU	
l	Н	G	F	E	D	C	

