	т	m		0			
Z'	ØS						
	I			LAY	OUT SHOWN AS EXAMPLE		
	Keying Shown as e	xample					
CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III -Shell Material : Composite -Shell Plating : Olive drab Cadmium		Connector dimensionDimNominalØS41.7 MaxZ'31.5 Max/V THREADM31x1-6g			ot be liable for any non-confor		
-Insulator : Thermoplastic -Contacts : Copper Alloy		IV THREAD IVISIXI-og		the Specifications	issued by either of the Parties	or by a third party	
-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8μm minimum					Country Ju FR	risdiction & Control List Not Listed	
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories				Р	N: 8D521J39BD		
-Temperature Range : -65°C to +175°C -Salt Spray : 2000 hours			A 07-10-2	016 First Release			
Mass : 57.1 g ± 10%			ISS DATE Designed By:	E Latest modification Date:	n - by	CUSTOMER DRAWING	MOD N°
			TITLE		Composite Plug	g 8D series	
BASIC SERIES: 8D 5 - 21 J SHELL TYPE : Plug with RFI Shielding	39 B D		SCALE		General linear Tolerances: ±	NPRDS / PROJECT 859	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 21		ORIENTATION : D CONTACT TYPE : SOCKET(500 Matings)	SOURIA	WWW.	SOURIAU.COM	This document is the pro SOURIAU it must not be reprodu	iced or
PLATING : J = Olive drab Cadmium		CONTACT TYPE : SOCKET(SOU Matings)	FORMAT A3		SOURIAU DRG N		SHEET 1/2
					8D521J39BD-C		1/2

