| т (О Т   | m                                     |  | 0                                 | σ            |                                  |        |
|--|---------------------------------------|--|-----------------------------------|--------------|----------------------------------|--------|
| Z'   |                                       |  |                                   |              |                                  |        |
|  |                                       |  | LAYOUT SHOW                       | N AS EXAMPLE |                                  |        |
| Keyir  | g Shown as example                    |  |                                   |              |                                  |        |
| CHARACTERISTICS  | Connector dimension Dim Nominal       |  |                                   |              |                                  |        |
| -Standard : Based on MIL-DTL-38999 Series III-Shell Material: Composite-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer | ØS41.7 MaxZ'31.5 MaxVV THREADM31x1-6g | SOURIAU shall not be liable for any non-conformity or damage<br>due to a use of the Products which does not comply with<br>the Specifications issued by either of the Parties or by a third party<br>(professional recommendation, technical notice.)<br>Country Jurisdiction & Control List |                                   |              |                                  |        |
| -Contact Plating : Gold over copper Alloy 0.8µm minimum  |                                       | FR     Not Listed  |                                   |              |                                  |        |
| -Durability : 500 Mating cycles<br>-Delivered with Souriau contacts and Accessories  |                                       | PN: 8D521M41AC   |                                   |              |                                  |        |
| -Temperature Range : -65°C to +200°C   |                                       |  | A 08-10-2016 First Release        |              |                                  |        |
| -Salt Spray : 2000 hours   |                                       |  |                                   |              |                                  |        |
| -Mass : 35.3 g ± 10%   |                                       | ISS DATE<br>Designed By:   | Latest modification - by<br>Date: | CUS          | TOMER DRAWING                    | MOD N° |
|  |                                       | TITLE Composite Plug 8D series   |                                   | ries         |                                  |        |
| BASIC SERIES: 8D 5 - 21 M 41 A   | c                                     | SCALE  | General I<br>Toleran              |              | IPRDS / PROJECT<br><b>859</b>    |        |
| SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact   | ORIENTATION : C                       |  |                                   |              | This document is the property of |        |
| SHELL SIZE : 21  | CONTACT TYPE : PIN(500 Matings)       | SOURIAL  | SOURIAU WWW.SOURIAU.COM           |              |                                  |        |
| PLATING : M = Nickel   | CONTACT TYPE : PIN(SOU Matings)       |  |                                   | SHEET        |                                  |        |
|  | CONTACT LATOUT . 21-41                | A3   |                                   | 1M41AC-C     |                                  | 1/2    |
|  |                                       |  | 0000                              |              |                                  |        |

|          | т  | ۵  | г   | m |                          | 0  |     |
|----------|----|--|-----|---|--------------------------|--|-----|
|          |    |  |     |   |                          |  |     |
|          |    | Contact Layout   |     |   |                          |  |     |
|          |    |  |     |   |                          |  |     |
|          |    |  |     |   |                          |  |     |
| 4        |    | +Y<br>7 HOLES  |     |   |                          |  |     |
|          | <  | 31   |     |   |                          |  |     |
|          |    |  |     |   |                          |  |     |
|          |    | X + (1 + (1 + (1 + (1 + (1 + (1 + (1 + (   |     |   |                          |  |     |
|          |    |  |     |   |                          |  |     |
|          |    |  |     |   |                          |  |     |
|          |    | 635 DIA  |     |   |                          |  |     |
|          |    |  | 7   |   |                          |  |     |
| ယ        |    | Insert arrangement 21-41           ber of         Size         Service         Contact         Supersedes           lacts         contacts         rating         location         1           1         20         I         All         MS20055-41 | -   |   |                          |  |     |
|          |    | · · · · · · · · · · · · · · · · · · ·  | _   |   |                          |  |     |
|          |    |  |     |   |                          |  |     |
|          |    |  |     |   |                          |  |     |
|          |    |  |     |   |                          |  |     |
|          |    |  |     |   |                          | SOURIAU shall not be liable for                                    |     |
|          |    |  |     |   |                          | due to a use of the Products<br>the Specifications issued by eithe |     |
|          |    |  |     |   |                          | (professional recommen   | ıda |
|          |    |  |     |   |                          |  | unt |
| N        |    |  |     |   |                          |  | -R  |
|          |    |  |     |   |                          | PN: 8D52   | 11  |
|          |    |  |     |   |                          | 116 First Release  |     |
|          |    |  |     |   |                          |  |     |
|          |    |  |     |   | ISS DATE<br>Designed By: | Latest modification - by<br>Date:                                  |     |
|          |    |  |     |   | TITLE                    | Com  | n   |
|          |    |  |     |   |                          |  |     |
|          |    |  |     |   | SCALE                    | General linea<br>Tolerances:                                       |     |
| <b>_</b> |    |  |     |   | NA                       |  |     |
|          |    |  |     |   | SOURIA                   | U WWW.SOURIAU  | J.( |
|          |    |  |     |   |                          |  |     |
|          |    |  |     |   | FORMAT<br>A3             | SOURIA   |     |
|          | Н  | G  | F   | E |                          | 8D521  | IV  |
|          | 11 |  | I I |   |                          |  |     |

