Ξ	۵	г	п			O	Φ	A		7
	Z	ØS								-
						LAYOUT SHO	WN AS EXAMPLE			
		Keying Show	n as example							
CHARACTERISTICS			Connector dimension							
-Standard : Based on	MIL-DTL-38999 Series III		Dim Nominal							
-Shell Material -Shell Plating -Insulator -Contacts	-Shell Plating : Olive drab Cadmium 2 31 Max -Insulator : Thermoplastic VV THREAD M31x1-6g				SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)					
-Seals & Grommet	: Silicon Elastomer	mum					Country Jurisd	iction & Control List Not Listed]	
 Contact Plating : Gold over copper Alloy 0.8μm minimum Durability : 500 Mating cycles 										
-Delivered without Sc	uriau contacts					PN: 8D	521W41SEL			
-Temperature Range	-				A 10-10-201	6 First Release				
-Salt Spray	: 500 hours				ISS DATE				MOD N°	_
– -Mass	: 43.78 g ± 10%				Designed By:	Latest modification - by Date:		CUSTOMER DRAWING		_
				TITLE	TITLE Aluminium Plug 8D series					
BASIC SERIES:	8D 5 - 21	L W 41 S E	L		SCALE	Gener	al linear	NPRDS / PROJECT		
SHELL TYPE : Plug wi				W/O Contacts	NA		ances:	859		
								This document is the prop SOURIAU	perty of	—
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 21				SOURIAU WWW.SOURIAU.COM it must not be reproduced communicated without permis						
SHELL SIZE : 21 CONTACT TYPE : SOCKET(500 Matings) PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 21-41					FORMAT		RIAU DRG N°	communicated without pe	SHEET	
$P[\Delta][N(r_{1} \cdot N)] =$			CONTACT L		A3					
PLATING : W =					AD		21W41SEL-C		1/2	

ſ	I	G	н г	m		0
		Contact Layout				
4		+Y				
	<	31° 23 31° 41' - 13 HOLES 10° - 20 HOLES				
			_			
ω	size no. con	Insert arrangement 21-41 ber of Size Service Contact Supersedes tacls contacts rating location 10 11 20 I All MS20055-41	-			
	F					SOURIAU shall not be liable for ar
						due to a use of the Products w the Specifications issued by either o
						(professional recommenda
N						Count FR
						PN: 8D521V
					A 10-10-20	116 First Release
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Alumir
					SCALE	General linear Tolerances:
_					NA	
					SOURIA	
					FORMAT A3	SOURIAU 8D521W
l	Н	G	F	E	D	C

4	-					
3						
r any non-conformity or damage s which does not comply with er of the Parties or by a third party ndation, technical notice.)						
Untry Jurisdiction & Control List FR Not Listed LW41SEL						
MOD N°	_					
customer drawing						
ar NPRDS / PROJECT						
	1					
J.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission						
V DRG N°SHEETW41SEL-C2/2						
B A						

ω