т родина и тородина и поредина и пореди И поредина и по	
Keying Shown as example	LAYOUT SHOWN AS EXAMPLE
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer	Imal Max Max Max SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)
-Contact Plating: Gold over copper Alloy 0.8μm minimum-Durability: 500 Mating cycles-Delivered with Souriau contacts and Accessories	Country Jurisdiction & Control List FR Not Listed PN: 8D521W72SA
-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours	A 10-10-2016 First Release MOD N° ISS DATE Latest modification - by MOD N° Designed By: Date: CUSTOMER DRAWING
BASIC SERIES: 8D 5 - 21 W 72 S A	TITLE Aluminium Plug 8D series SCALE General linear NA Image: Constraint of the series NA Image: Constraint of the series
	ORIENTATION : A SOURIAU E OCKET(500 Matings) VWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission
PLATING : W = Olive drab Cadmium	ACT LAYOUT : 21-72 FORMAT A3 SOURIAU DRG N° SHEET 1/2

	т	۵	г	m	D	0
4		Contact Layout 72				
		2#4 Power				
	Ctc	6#16 21-72 X Y				
	A B C D	0 6.19 8.5 4.3 6.25 0 8.5 -4.3	-			
ى ت	E F G	0 -6.19 -8.5 -4.3 -6.25 0	- - -			
	н	-8.5 4.3				SOURIAU shall not be liable for any
						due to a use of the Products wh the Specifications issued by either of (professional recommendat
N						PN: 8D521V
					A 10-10-201 ISS DATE	L6 First Release Latest modification - by
					Designed By: TITLE	Date: Alumin
_					SCALE NA	General linear Tolerances: ±
					FORMAT	J WWW.SOURIAU.C SOURIAU
			1		A3	8D521W
	Н	G	F F	E	D	C

