ד ₪ T	m		0	₩	Þ		
Keying Show	vn as example		LAYOUT SHOWN AS EX	AMPLE			
-Standard : Based on MIL-DTL-38999 Series III Dim Nominal -Shell Material : Aluminium ØS 41.7 Max -Shell Plating : Olive drab Cadmium Z 31 Max -Insulator : Thermoplastic VV THREAD M31x1-6g -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer			SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
-Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D521W	Not Listed			
-Temperature Range <u>-</u> -65°C to +175°C -Salt Spray : 500 hours		A 10-10-2016 ISS DATE Designed By:	First Release Latest modification - by Date:	CUSTOME	MOD N° R DRAWING		
BASIC SERIES: 8D 5 - 21 W 72 S C		SCALE	General linear Tolerances:		/ PROJECT 359		
SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 21	ORIENTATION : C CONTACT TYPE : SOCKET(500 Matings)	NA ± asy SOURIAU WWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission		cument is the property of SOURIAU st not be reproduced or nicated without permission			
PLATING : W = Olive drab Cadmium	CONTACT LAYOUT : 21-72	FORMAT A3	SOURIAU 8D521W2		SHEET		

besigned By: bate: A bottom of the second		Ŧ	۵	п П	m		0
72 244 Power 6#16 10 10 10 10 10 10 10 10 10 10 10 11 12 12 13 14 15 16 17 18 19 10 10 10 10 10 11 12 12 13 14 15 16 17 18 19 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10			Contact louget				
C 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2							
24 Рожег 64 16 16 10			12				
244 Power 6+16 Σ2-72 Cte X 8 8.5 0 8.5 0 8.5 0 8.5 0 8.5 0 8.5 0 8.5 0 8.5 0 8.5 0 8.5 0 8.5 0 8.5 0 8.5 0 8.5 0 8.5 0 8.5 0 8.5 0 9.5 0 9.5 0 9.5 0 9.5 0 9.5 0 9.5 0 9.5 0 9.5 0 9.5 0 9.5 0 9.5 0 9.5 0 9.5 0 9.5 0 9.5 0 9.5 0 9.5<	4						
24 Power 64 16							
C Ctc X Y A 0 6.19 B 8.5 4.3 C 6.25 0 D 8.5 4.3 C 6.25 0 H -8.5 -4.3 C -6.25 0 N Correct lows Web Specification issued by ether ignoresional recommon ignost the folduces Image: Notation is the specification issued by ether ignoresional recommon ignost the folduces Endegree for ignost in the specification is by intersection issued by ether ignoresional recommon ignost in the specification is by intersection issued by ether ignost in the specification is by intersection issued by ether ignost in the specification is by intersection issued by ether ignost in the specification is by intersection issued by ether ignost in the specification is by intersection issued by ether ignost in the specification is by intersection issued by ether ignost in the specification is by intersection issued by ether ignost in the specification is by intersection is by intersection is							
Image: constraint of the constrated of the constraint of the constraint of the constraint of the							
C C C C C C C C C C C C C C C C C C C		[1			
A 0 6.19 B 8.5 4.3 C 0 6.19 F -8.5 -4.3 G -6.25 0 H -8.5 4.3 G -6.25 0 H -8.5 4.3		Ctc		-			
Со С С С С С С С С С С С С С]			
C D 8.5 -4.3 E 0 -6.13 F -8.5 -4.3 G -6.25 0 H -8.5 -4.3 G -6.25 0 H -8.5 -4.3 G -6.25 0 H -8.5 -4.3 SOURAU shall not be lable for a use of the Products with specifications issued by ether (professional recommend) Image: Commend of the product with the specification is used the Product with the specification is used the Product with the specification is used by ether (professional recommend) Image: Commend of the product with the product with the specification is used the Product with the specification is used by ether (professional recommend) Image: Commend of the product with the specification is used the product with the product with the product with the product wit							
E 0 -6.19 F -8.5 -4.3 G -6.25 0 H -8.5 4.3 SOURIAU shall not be liable for a use of the Products with specification issued by either (professional recommend) Image: Control of the product set of the produc				-			
F -8.5 -4.3 G -6.25 0 H -8.5 4.3 SOURIAU shall not be itable for a due to a use of the Products with the Specification sized by either (professional recommend) Image: Colspan="2">Counting the Specification of the Product shall not be itable for a use of the Product shall not be used by the itable for a use of the Product shall not be used by the use of the Product shall not be used by the use of the Product shall not be used by the use of the Product shall not be used by the use of the Product shall not be used by the use of the Product shall not be used by the use of the Product shall not be used by the use of the Product shall not be used by the use of the Product shall not be used by the use of the Product shall not be used by the use of the use of the Product shall not be used by the use of the Product shall not be used by the use of the use of the Product shall not be used by the use of the use of the us	ယ						
G -6.25 0 H -8.5 4.3 SOURIAU shall not be liable for a use of the Products we the Specifications issued by either the Specifications issued by either the Specification sized by either the				-			
H -8.5 4.3 SOURIAU shall not be liable for all due to a use of the Products with the Specification issued by either (professional recommend) Image: Source of the Specification issue of the				-			
besigned By: bate: A bottom of the second]			
besigned By: bate: A bottom of the second		I					
besigned By: bate: A bottom of the second							SOURIAU shall not be liable for any
(professional recommendation of the second s							due to a use of the Products wh
PN: 8D521 PN: 8D521 A 10-10-2016 First Release ISS DATE Latest modification - by Designed By: Date: TITLE Alumit SCALE General linear Tolerances: ± SOURIAU A3 SOURIAU.							the Specifications issued by either of (professional recommendat
PN: 8D521 PN: 8D521 A 10-10-2016 First Release ISS DATE Latest modification - by Designed By: Date: TITLE Alumit SCALE General linear Tolerances: ± SOURIAU A3 SOURIAU.							Countr
A 10-10-2016 First Release ISS DATE Latest modification - by Designed By: Date: TITLE Alumin SCALE NA Control of the second	N					[FR
ISS DATE Latest modification - by Designed By: Date: TITLE Alumin SCALE NA General linear Tolerances: ± SOURIAU FORMAT SOURIAU. A3 SOURIAU							PN: 8D521V
ISS DATE Latest modification - by Designed By: Date: TITLE Alumin SCALE NA General linear Tolerances: ± SOURIAU FORMAT SOURIAU. A3 SOURIAU							
Designed By: Date: TITLE Alumin SCALE NA General linear Tolerances: ± SOURIAU A3 SOURIAU A3 SOURIAU							
SCALE NA SOURIAU SOURIAU FORMAT A3 SOURIAU SOURIAU A3 SOURIAU SOURIAU A3 SOURIAU							
SCALE NA SOURIAU SOURIAU FORMAT A3 SOURIAU SOURIAU A3 SOURIAU SOURIAU A3 SOURIAU						TITLE	Alumin
NA TOlerances: ± SOURIAU WWW.SOURIAU.(A3 SOURIAL A3 SD521W							
FORMAT SOURIAU A3 8D521W						SCALE	
FORMAT SOURIAL A3 8D521V	<u> </u>					NA	
A3 8D521W						SOURIA	U WWW.SOURIAU.C
A3 8D521W						FORMAT	
							8D521W
	l	Н	G	F	E	D	C

