	т п		0	₿ >	
A Thread Contraction of the second se					4
			LAYOUT SHOWN AS EXAMP	LE	3
	Keying Shown as example				
CHARACTERISTICS	Connector dimension	1			
-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal				
-Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer Contact Plating : Cold over copper Alloy 0.8um minimum	ØS41.7 MaxZ31 MaxVV THREADM31x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed		
 Contact Plating : Gold over copper Alloy 0.8μm minimum Durability : 500 Mating cycles Delivered with Souriau contacts and Accessories 			PN: 8D521W77BA		
-Temperature Range : -65°C to +175°C		A 10-10-2016	First Release		
-Salt Spray : 500 hours					100.00
		ISS DATE Designed By:	Latest modification - by Date:		MOD N°
		TITLE	TITLE Aluminium Plug 8D series		
→ BASIC SERIES: 8D 5 - 21 W 77 → SHELL TYPE : Plug with RFI Shielding	B A	SCALE -	General linear Tolerances: ±	NPRDS / PROJECT 859	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 21	ORIEN CONTACT TYPE : SOCKET(50	ITATION : A SOURIAU	WWW.SOURIAU.COM	This document is the property SOURIAU it must not be reproduced or communicated without permiss	r
PLATING : W = Olive drab Cadmium	CONTACT LAYO		SOURIAU DR		SHEET
		A3	8D521W77		1/2
	1				

	Ŧ	Q	П	П		0
4		Contact Layout				
		17#22D				
		2#8 Triax	_			
		21-77				
	Ctc	X Y				
	A	1.96 8.38	_			
	В	5.46 7.67	_			
	c	8.51 5.79	_			
ω	D	10.46 2.82	-			
	E F	10.46 -2.82 8.51 -5.79	-			
	G	5.46 -7.67	-			
	н	1.96 -8.38	-			
		0 -5.41	-			
-	К	-1.96 -8.38	\neg			
	L	-5.46 -7.67				SOURIAU shall not be liable for any due to a use of the Products whi
	M	-8.51 -5.79				the Specifications issued by either of
	N	-10.46 -2.82				(professional recommendation
	P	-10.46 2.82				
N	R	-8.51 5.79				Country FR
	S	-5.46 7.67				
	Т	-1.96 8.38				PN: 8D521W
	U	-4.57 0	_			
	V	4.57 0			A 10-10-20	16 First Release
					ISS DATE	Latest modification - by
					Designed By:	Date:
					TITLE	Alumini
→					SCALE NA	General linear Tolerances: ±
					SOURIA	U WWW.SOURIAU.Co
					FORMAT A3	SOURIAU 8D521W7
·	Н	G	F	E	D	C
					V	

