	Q	П	т		D	0	σ	A		
	Z	ØS								
2						LAYOUT SH	IOWN AS EXAMPLE			3
		Keying Shown	as example							
CHARACTERISTICS		Г	Connector dimension	_						
-Standard : Based on MIL-DTL-	8999 Series III	-	DimNominalØS41.7 Max							
-Insulator : Ther -Contacts : Copp	oosite out Plating noplastic er Alloy n Elastomer		Z 31 Max VV THREAD M31x1-6g			due to a use of the P the Specifications issued	able for any non-conformity or roducts which does not compl by either of the Parties or by a ommendation, technical notic Country Jurisdictio	y with third party		
-Contact Plating : Gold	over copper Alloy 0.8µm minimum				·			ot Listed		
-Delivered with Souriau contac						PN: 8	D521X48PD			
-Temperature Range : -65° -Salt Spray : 2000	to +175°C				A 11-10-2	2016 First Release				
	g ± 10%				ISS DAT		1		MOD N°	+
					Designed By:	Date:	C	USTOMER DRAWING		-
					TITLE		Composite Plug 8D s	eries		
BASIC SERIES:		X 48 P D			SCALE NA		eral linear erances: ±	NPRDS / PROJECT <b>859</b>		_
CONTACT TYPE : Standard C SHELL SIZE : 21	imp Contact		OR CONTACT TYPE : PIN	IENTATION : D	SOURIA	AU WWW.SOU	RIAU.COM	This document is the prope SOURIAU it must not be reproduce communicated without perr	d or	
PLATING : X = Withou	Plating			AYOUT : 21-48	FORMAT	<u> </u>	JRIAU DRG N°		SHEET	_
	<u> </u>	<b>I</b>			A3		0521X48PD-C		1/2	
				1	1					1

	т	۵	нт. П	m	0	
		Contact Layout				
		48				
4	-×					

F

Е

G

Н

4#8 Power

21-48				
x	Y			
4.57	4.57			
4.57	-4.57			
-4.57	-4.57			
-4.57	4.57			
	X 4.57 4.57 -4.57			

ယ

 $\sim$ 

due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country FR PN: 8D521X48PD A 11-10-2016 First Release DATE Latest modification - by ISS Designed By: Date: TITLE SCALE General linear  $( \bigcirc$ Tolerances: NA ±---**SOURIAU** WWW.SOURIAU.COM FORMAT A3 С D

