	т (О)				
4		4 International International			
3		LAYOUT SHOWN AS EXAMPLE 3			
	Keying Shown as example				
	CHARACTERISTICS Connector dimension				
2	Standard : Based on NIL-DTL-38999 Series III   Dim   Nominal     -Shell Material   : Aluminium   ØS   41.7 Max     -Shell Plating   : Black Zinc Nickel   Z   31 Max     -Insulator   : Thermoplastic   VV THREAD   M31x1-6g     -Contacts   : Copper Alloy   : Solicon Elastomer				
	-Durability : 500 Mating cycles -Delivered without Souriau contacts	FR     Not Listed     2       PN: 8D521Z42SNL     2			
	-Temperature Range : -65°C to +175°C	A 12-10-2016 First Release			
	-Salt Spray : 500 hours	ISS DATE Latest modification - by MOD N°			
ĺ		Designed By: Date: CUSTOMER DRAWING   TITLE Aluminium Plug 8D series			
	BASIC SERIES: 8D 5 - 21 Z 42 S N L   SHELL TYPE : Plug with RFI Shielding      Delivered W/O	SCALE General linear NPRDS / PROJECT Tolerances: 859			
	ATION : N Matings) SOURIAU WWW.SOURIAU.COM				
	SHELL SIZE : 21   CONTACT TYPE : SOCKET(500     PLATING : Z = Black Zinc Nickel   CONTACT LAYOU	IT : 21-42 FORMAT SOURIAU DRG N° SHEET			
		A3 8D521Z42SNL-C 1/2			

_	т	Q	<del>ات</del>	m		0
4		Contact Layout 42				
_	Ctc A B	2#4 Power 21-42 X Y 0 6.19 0 -6.19				
ယ						
	_					SOURIAU shall not be liable for an due to a use of the Products wi the Specifications issued by either o (professional recommenda
N						PN: 8D5212
					ISS DATE Designed By:	Date:
_					SCALE NA	Alumir General linear Tolerances: ±
					FORMAT A3	U WWW.SOURIAU.C SOURIAU 8D521Z4
L	Н	G	F	E	D	C

