		т	m	D	0			
ARACTERSTCS         Shadrar : saved mULoTL:33999 Series II:         Shell Material ::       Connector dimension         How to report allow								
CHARACTERISTICS         -Standard: Based on MIL-DTI-38999 Series III         -Shell Material       : Composite         -Shell Yere       : Composite         -Shell Yere       : Composite         : Shell Yere       : Shell Shelling </td <td></td> <td></td> <td></td> <td></td> <td>LAYOUT SHO</td> <td>OWN AS EXAMPLE</td> <td></td> <td></td>					LAYOUT SHO	OWN AS EXAMPLE		
Standard: Eased on MIL DTL-38999 Series III       Dimeted or minimal dots         Shell Material       : Composite         Shell Material       : Olive drab Cadmium         Shell Material       : Olive drab Cadmium         Insulator       : Dimeted or minimal dots         - Shell Material       : Olive drab Cadmium         Insulator       : Dimeted or minimal dots         - Shell Material       : Olive drab Cadmium         - Shell Material       : Olive drab Cadmium         - Shell Plating       : Sold over copper Alloy         - Seals & Grommet       : Silicon Flastomer         - Contact Plating       : Sold Naire cycles         - Delivered with Souriau contacts and Accessories       -         - Temperature Range       : - Olive drab Sale of the Prates on the second control List         - Shell TYPE       : Slandard Crimp Contact         SHELL TYPE       : Slandard Crimp Contact         SHELL TYPE       : Slandard Crimp Contact         SHELL SIZE       : Souriau         ORIENTATION : D       ORIENTATION : D         ORIENTATION : D       CONTACT TYPE : Slandard Crimp Contact         SHELL SIZE       : Souriau       WWW.SOURIAU.COM         The doncate or communicated with with entergenerindificator       Souriau         <		Keying Shown as	s example					
Shell Material       i Composite         Contact Shell Gover copper Alloy 0.8µm minimum       i Composite         -Derivered with Souriau contacts and Accessories       PN: 8D523J06PD         -Temperature Range       - 65°C to +175°C         -Satt Spray       : 2000 hours         BASIC SERIES:       80       5         SHELL TYPE       : Stell TYPE         SHELL TYPE       : Stell TYPE         SHELL SIZE       : Sandard Crimp Contact         SHELL SIZE       : Contact Crimp Contact <t< td=""><td></td><td>E</td><td>Dim Nominal</td><td></td><td></td><td></td><td></td><td></td></t<>		E	Dim Nominal					
-Contact Plating       : Gold over copper Alloy 0.8µm minimum         -Durability       : 500 Mating cycles         -Delivered with Souriau contacts and Accessories         -Temperature Range       : -65°C to +175°C         -Salt Spray       : 2000 hours         A       06-10-2016         BASIC SERIES:       8D         SHELL TYPE       : Plug with RFI Shielding         CONTACT TYPE       : Stald and Crimp Contact         SHELL SIZE : 23       . 06         PLATING       . J         ORIENTATION : D       SOURIAU         SHELL SIZE : 23       . 06         PLATING       . J         PLATING	-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy		Z' 31.5 Max		due to a use of the Pr the Specifications issued b	oducts which does not com y either of the Parties or by	ply with a third party	
-Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +175°C -Salt Spray : 2000 hours -Salt Spray : 2000 hours BASIC SERIES: 80 5 - 23 J 06 P D SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 23 PLATING : J = 0 live drab Cadmium CONTACT TYPE : Plug with RFI Shielding PLATING : J = 0 live drab Cadmium CONTACT TYPE : Plug with RFI Shielding PLATING : J = 0 live drab Cadmium CONTACT TYPE : 23-0 PLATING : J = 0 live drab Cadmium CONTACT TYPE : 23-0 PLATING : J = 0 live drab Cadmium CONTACT TYPE : 23-0 PLATING : J = 0 live drab Cadmium CONTACT TYPE : 23-0 PLATING : J = 0 live drab Cadmium CONTACT TYPE : 23-0 PLATING : J = 0 live drab Cadmium CONTACT TYPE : 23-0 PLATING : J = 0 live drab Cadmium CONTACT TYPE : 23-0 PLATING : J = 0 live drab Cadmium CONTACT TYPE : 23-0 PLATING : J = 0 live drab Cadmium CONTACT LAYOUT : 23-06 CONTACT TYPE : 23-0 PLATING : J = 0 live drab Cadmium CONTACT TYPE : 23-0 PLATING : J = 0 live drab Cadmium CONTACT TYPE : 23-0 PLATING : J = 0 live drab Cadmium CONTACT TYPE : 23-0 PLATING : J = 0 live drab Cadmium CONTACT TYPE : 23-0 CONTACT TYPE : 23-0 CONTACT LAYOUT : 23-06 CONTACT TYPE : 23-0 CONTACT LAYOUT : 23-06 CONTACT TYPE : 23-0 CONTACT LAYOUT : 23-06 CONTACT TYPE : 23-0 CONTACT LAYOUT : 23-06 CONTACT CONTACT LAYOUT : 23-06 CONTACT LAYOUT : 23-06 CONTACT LAYOUT : 23-06 CONTACT CONTACT LAYOUT : 23-06 CONTACT LAYOUT : 23-								
-Salt Spray : 2000 hours -Salt Spray : 2000 hours A 06-10-2016 First Release ISS DATE Latest modification - by Designed By: Date: CUSTOMER DRAWING Designed By: Date: CUSTOMER DRAWING Designed By: Date: CUSTOMER DRAWING TITLE Composite Plug 8D series SCALE NA SSCALE SCALE NA SSCALE NA SSCALE NA SOURIAU WWW.SOURIAU.COM This document is the property of SOURIAU It must not be reproduced or communicated without permission FORMAT SOURIAU DRG N° SHEET SOURIAU DRG N° SHEET DESIGNED DESIGN					PN: 8	D523J06PD		
BASIC SERIES:       8D       5       23       J       06       P       D       D       TITLE       Composite Plug 8D series       SEGUE         BASIC SERIES:       8D       5       23       J       06       P       D       D       SCALE       General linear       NPRDS / PROJECT       SEGUE       SCALE       SCALE       NPRDS / PROJECT       SEGUE       SEGUE       SCALE       NPRDS / PROJECT       SCOURIAU       SCOURIAU       SCOURIAU       This document is the property of SOURIAU       SOURIAU       It must not be reproduced or communicated without permission         SHELL SIZE : 23       CONTACT TYPE : PIN(500 Matings)       CONTACT TYPE : PIN(500 Matings)       FORMAT       SOURIAU DRG N°       SHEET				A 06-10-20	16 First Release			
BASIC SERIES: 8D 5   SHELL TYPE: P   CONTACT TYPE: Standard Crimp Contact:   SHELL SIZE: 23   PLATING: J   ORIENTATION: D   CONTACT TYPE: PIN(500 Matings)   CONTACT TYPE: PIN(500 Matings)   CONTACT TYPE: SOURIAU   CONTACT TYPE: SOURIAU   WWW.SOURIAU.COM SOURIAU   It must not be reproduced or communicated without permission   CONTACT TYPE: PIN(500 Matings)   CONTACT TYPE: PIN(500 Matings)   CONTACT TYPE: PIN(500 Matings)   CONTACT TYPE: SOURIAU   WWW.SOURIAU.COM SOURIAU   It must not be reproduced or communicated without permission   CONTACT TYPE: PIN(500 Matings)   CONTACT TYPE: PIN(500 Matings)	-				-		CUSTOMER DRAWING	MOD N°
BASIC SERIES.       BASIC SERIES.<				TITLE		Composite Plug 8D	series	
CONTACT TYPE : Standard Crimp Contact       ORIENTATION : D         SHELL SIZE : 23       CONTACT TYPE : PIN(500 Matings)         PLATING : J = Olive drab Cadmium       CONTACT LAYOUT : 23-06		06 P D				rances:		
PLATING : J = Olive drab Cadmium       CONTACT LAYOUT : 23-06       FORMAT       SOURIAU DRG N°       SHEET	CONTACT TYPE : Standard Crimp Contact			SOURIA	U WWW.SOUI	RIAU.COM	SOURIAU it must not be reproduce	d or
							communicated without perr	
				. 25-00				

F	т	۵	г – – – – – – – – – – – – – – – – – – –	m		0
		Contact Layout				
4		06				
		6#8 Concentric				
		Twinax Service M				
_		23-06	]			
	Ctc	X Y	]			
	A	0 9.24	-			
	В	8.81 2.87	-			
	C	5.43 -7.49	-			
ယ	D E	-5.43 -7.49 -8.81 2.87	-			
	F	0 0	-			
	_					
						SOURIAU shall not be liable for an due to a use of the Products w the Specifications issued by either o (professional recommenda
N						Count FR
						PN: 8D523
					A 06-10-20	16 First Release
_					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Compo
_					SCALE	General linear Tolerances:
					SOURIA	U WWW.SOURIAU.
					FORMAT	
					A3	SOURIAU 8D523J
L	Н	G	F	I E	D	C

