

F

CONTACT TYPE	: Standard Crimp Contact
SHELL SIZE : 25	

PLATING : S = Nickel

Н

G

SOURIAU

FORMAT

A3

D

ORIENTATION : D

CONTACT LAYOUT : 25-61

CONTACT TYPE : SOCKET(500 Matings)

Е

0	ω	A			
				4	
LAYOUT SHOWN AS	EXAMPLE			3	
URIAU shall not be liable for a due to a use of the Products w pecifications issued by either o (professional recommenda Count FR PN: 8D525	which does not co of the Parties or I ation, technical n try Jurisd	mply with by a third party		2	
elease st modification - by Date:		CUSTOMER DRAWING	MOD N°		
Stainless Steel Plug 8D series					
General linear Tolerances: ±		NPRDS / PROJECT 859		1	
WWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission					
SOURIAU 8D525S	J DRG N° 61BD-C		SHEET 1/2		
С	В	A	·	,	

	Т	Q	٦	m	D	C	Φ	A		
		Contact Layout								
4	ev By Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision Supervision	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	_							4
	B +.314 (7.98) + C +.413 (10.49) + D +.485 (12.32) + E +.527 (13.39) +	Y-axis (mm) Contact position ID X-axis (mm) Y-axis (mm) .500 (12.70) i +.251 (6.38) 314 (7.98) .435 (11.05) j +.133 (3.38) 379 (9.63) .343 (8.71) k +.000 (0.00) 402 (10.21) .230 (5.84) m 133 (3.38) 379 (9.63) .101 (2.57) n 251 (6.38) 314 (7.98)								
ω	G +.511 (12.98) H +.454 (11.53) J +.368 (9.35) K +.259 (6.58) L +.134 (3.40) M +.000 (0.00) N 134 (3.40) P 259 (6.58) R 368 (9.35) S 454 (11.53) T 511 (12.98) U 536 (13.61) V 527 (13.39) W 485 (12.32) X 413 (10.49)	$\begin{array}{c c c c c c c c c c c c c c c c c c c $								3
	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	435 (11.05) FF 237 (6.02) +.122 (3.10) .500 (12.70) GG 147 (3.73) +.223 (5.66) .454 (11.53) HH +.000 (0.00) +.200 (5.08) .454 (11.53) JJ +.105 (2.67) +.094 (2.39) .363 (9.22) KK +.135 (3.43) 041 (1.04) .283 (7.19) LL +.000 (0.00) 132 (3.35) .175 (4.45) MM 135 (3.43) 041 (1.04) .046 (1.17) NN 105 (2.67) 094 (2.39) .088 (2.24) PP +.000 (0.00) +.000 (0.00) .135 (3.43) 041 (1.04) .040 (1.104) .040 (1.104) .046 (1.17) NN 105 (2.67) .0694 (2.39) .088 (2.24) PP +.000 (0.00) +.000 (0.00) .213 (5.41)								
	ShellArrangementNumbsizeno.conta25-6161	er of Size Service Contact Superseder icts contacts rating location All MS20057-6	3 1			SOURIAU shall not be liable for due to a use of the Products the Specifications issued by eithe (professional recommer	s which does not comply w	ith		
N							Intry Jurisdiction 8 FR Not L			2
						PN: 8D52	5S61BD			
					A 08-10-20	016 First Release				
					ISS DATE Designed By:	Latest modification - by Date:	CUST	OMER DRAWING	MOD N°	
					TITLE	Stainle	ess Steel Plug 8D se	eries		
					SCALE	General line Tolerances		RDS / PROJECT 859		
					SOURIA	U WWW.SOURIAL	J.COM	his document is the proper SOURIAU it must not be reproduced mmunicated without perm	l or	1
					FORMAT A3		U DRG N°		SHEET	
l	Н	G	F	E		C 8D525	B B B	A	<i>2 2</i>	J