	T Q T	m	C	כ	0	B	A		_
4 3		S			<image/>	YOUT SHOWN AS EXAMPLE			4
	Keying	Shown as example							
	CHARACTERISTICSStandard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal							
	-Shell Material: Aluminium-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy	A 34.9±0.3 B 19.07+0.1/-0.15 R 32.5Max S 31.8±0.4 W 2.2+0.9/-0.1 VV THREAD M15x1-6g			due to a use the Specifications	not be liable for any non-confo of the Products which does no s issued by either of the Parties ional recommendation, technic	nt comply with s or by a third party		
N	-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum	·				Country Ju FR	risdiction & Control List Not Listed		2
	-Durability : 500 Mating cycles -Delivered without Souriau contacts				P	N: 8D711F02SBL			
	-Temperature Range : -65°C to +200°C -Salt Spray : 48 hours						_		
	-Mass : 18.78 g ± 10%			ISS DATE Designed By:	Latest modification	· · · · · · · · · · · · · · · · · · ·	CUSTOMER DRAWING	MOD N°	$\left - \right $
				TITLE		Aluminium Recept	acle 8D series		
_	BASIC SERIES: 8D 7 - 11 F 02 S	B L	Contosta	SCALE		General linear Tolerances: ±	NPRDS / PROJECT 859		
	SHELL TYPE : Jam nut Receptacle CONTACT TYPE : Standard Crimp Contact	Delivered W/O ORIENTA				.SOURIAU.COM	This document is the pro SOURIAU		$\left \right ^{\prime}$
	SHELL SIZE : 11	CONTACT TYPE : SOCKET(500	Matings)	FORMAT			it must not be reprodu communicated without p	ermission	
	PLATING : F = Nickel	CONTACT LAYOU	JT : 11-02	A3		SOURIAU DRG N 8D711F02SBL-(SHEET	
L	H G F	E	C)	C	В	A	1	

ſ	ت D	п		_				
4	Contact Layout							
	Contacts (Insert arrangement 11-2) Contact position ID X-axis (mm) Y-axis (mm) A +.095 (2.41) +.000 (.00) B 095 (2.41) +.000 (.00) Shell Arrangement no. Number of contacts Size rating Contact location 11 -2 2 16 I All		Dim Nominal B 19.59+0/-0.25					
3			ØC 20.96+0.25/-0	3				
2			SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)	2				
			PN: 8D711F02SBL A 30-09-2016 First Release					
			ISS DATE Latest modification - by MOD N° Designed By: Date: CUSTOMER DRAWING TITLE Aluminium Receptacle 8D series					
_			SCALE General linear NPRDS / PROJECT NA Image: Tolerances: 1mm ± Image: This document is the property of SOURIAU SOURIAU SOURIAU Image: This document is the property of source or communicated without permission	1				
			FORMATSOURIAU DRG N°SHEETA38D711F02SBL-C2/2					
	H G	F E	D C B A					