		T	G	т	m	D		0	B	A		_
CHARACTERISTIC Standard : Based on MIL-DTL-38099 Series II Schell Material ::::::::::::::::::::::::::::::::::::		t 22.6 Max t t t t t t t t								4		
Shell Material : Aluninium Shell Material : Aluninium Shell Plating : Nickel -insulator : Thermoplastic -insulator : Copper Alloy Seals & Grommet : Slicon Elastomer Contact Plating : Goid over copper Alloy 0.8µm minimum -Derivered with Source complex with does not comply with the Specification issued by eliment of the Parties on the partice on the parties on the partice on the parties on the parties on the partice on the parties on the parthead on the parties on the parthead on the			111	Keying Shown as	Connector dimension							
-Salt Spray : 48 hours -Mass : 21.05 g ± 10% BASIC SERIES: 8D 8D 7 11 F 04 5 07 11 F 04 07 11 08 07 11 F 04 5 07 11 08 7 10 11 08 7 11 F 04 5 07 11 11 F 04 5 08 7 11 F 04 5 08 7 11 F 04 5 08 7 11 11 11 11 12 11 13 11 14 11 14 11 15 12 16 12 17	2	-Shell Material: Aluminium-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper-Durability: 500 Mating cycles	Alloy 0.8µm minimum		B 19.07+0.1/-0.15 R 32.5Max S 31.8±0.4 W 2.2+0.9/-0.1			due to a use of the Pr the Specifications issued b (professional reco	oducts which does not com y either of the Parties or by mmendation, technical no Country Jurisdic FR	nply with / a third party tice.) ction & Control List		2
BASIC SERIES: 8D 7 11 F 04 S N SCALE SCALE Tolerances: 359 359 1 SHELL TYPE : Standard Crimp Contact ORIENTATION : N ORIENTATION : N SOURIAU This document is the property of SOURIAU SOURIAU it must not be reproduced or communicated without permission PLATING : F = Nickel CONTACT TYPE CONTACT LAYOUT : 11-04 FORMAT SOURIAU DRG N° SHEET SHEET A3 8D711F04SN-C 1/2		-Salt Spray : 48 hours				ISS	DATE	Latest modification - by		CUSTOMER DRAWING	MOD N°	-
SHELL TYPE : Jam nut Receptacle NA Tolerances: 859 CONTACT TYPE : Standard Crimp Contact ORIENTATION : N NA SOURIAU This document is the property of SOURIAU.COM SOURIAU SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOCKET(500 Matings) FORMAT SOURIAU DRG N° SHEET PLATING : F = Nickel CONTACT TYPE : 11-04 FORMAT SOURIAU DRG N° SHEET 1/2 1/2		BASIC SERIES: 8D	7 - 11 F	04 S N				Gene	ral linear			
A3 SOORIAO DRG N 1/2	→	SHELL TYPE : Jam nut Receptacle CONTACT TYPE : Standard Crimp Contact				ION : N SO		$\neg \Psi$	±	This document is the pro SOURIAU it must not be reprodu	ced or	1
			G	F	CONTACT LAYOUT :	A		8D	711F04SN-C	Λ		

Г	٦ D	יד (יד			
4	Contact Layout $ \begin{array}{c} $		Panel cutout JAM NUT RECEPTACLE (TYPE 7)	4	
	(Insert arrangement 11-4) Contact position ID Contact location A +.065 (1.65) +.065 (1.65) B +.065 (1.65) 065 (1.65) C 065 (1.65) 065 (1.65) D 065 (1.65) +.065 (1.65) Shell Arrangement NO. Number of contacts Size rating Service location Contact Supersedes 11 4 4 20 I All MS20050-4				
ω			DimNominalB19.59+0/-0.25ØC20.96+0.25/-0	3	
	_		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with		
N			the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed	2	
			PN: 8D711F04SN A 30-09-2016 First Release		
			ISS DATE Latest modification - by	MOD N°	
			Designed By: Date: CUSTOMER DRAWING TITLE Aluminium Receptacle 8D series		
_			SCALE General linear NPRDS / PROJECT NA ± 859		
			SOURIAU WWW.SOURIAU.COM This document is the product of the source of th	uced or	
			FORMAT SOURIAU DRG N° A3 8D711E04SN-C	SHEET 2/2	
	H G	FE	A3 8D711F04SN-C D C B A	<i>L L</i>	