	<b>T</b>	۵	г	П		D	0		σ	A		
4										4		
			Keying Shov	vn as example								
N	-Durability : 500 Mating -Delivered with Souriau contacts and	tic y omer opper Alloy 0.8µm minim cycles Accessories	um	Connector dimension     Dim   Nominal     A   34.9±0.3     B   19.07+0.1/-0.15     R   32.5Max     S   31.8±0.4     W   2.2+0.9/-0.1     VV THREAD   M15x1-6g			due to a use o the Specifications (professio	not be liable for any no of the Products which issued by either of the onal recommendation Country FR PN: 8D711F2	does not comply v e Parties or by a th , technical notice.) Jurisdiction Not	with ird party		2
	-Temperature Range : -65°C to +2 -Salt Spray : 48 hours	00 C				A 30-09-2	016 First Release					
	-Mass : 17.66 g ± 10	%				ISS DATE Designed By:	E Latest modificatio Date:	on - by	CUS	TOMER DRAWING	MOD N°	-
						TITLE		Aluminium R				-
	BASIC SERIES: SHELL TYPE : Jam nut Receptacle	8D 7 - 11	F 22 A N			SCALE NA		General linear Tolerances: ±		PRDS / PROJECT <b>859</b>		1
· · ·	CONTACT TYPE : Standard Crimp Contact   SHELL SIZE : 11 CONTACT TYPE : PIN(500 Matings)					- SOURIAU VV VV.SOURIAU.COIVI it must not be reproduced					ced or	
	PLATING : F = Nickel			CONTACT LA	YOUT : 11-22	format A3	I	SOURIAU D 8D711F22			SHEET 1/2	
	Н	G	F	E		D	С		В	А		-

ſ	I	۵	нт —	m	D	0	ω	A		
4		Contact Layout 22*				Panel cutout				4
ω	Ctc A B C D	11-22   X Y   1.905 1.905   1.905 -1.905   -1.905 -1.905   -1.905 1.905				Dim Nominal B 19.59+0/-0. ØC 20.96+0.25/	25			3
N						due to a use of the Pro the Specifications issued by (professional recon		with nird party		2
					A 30-09-2016 First Release   ISS DATE Latest modification - by   Designed By: Date: CUSTOMER DRAWING   TITLE Aluminium Receptacle 8D series   SCALE General linear   NA ±   This document is the proper				MOD N°	_ 1
	Н	G	F	E	FORMAT A3 D	SOU		SOURIAU it must not be reproduced communicated without perm		