	I	G	ТТ	m		0	D	A		
4	R 22.6 Max	N Thread		S			UT SHOWN AS EXAMPLE			4
			Keying Shown a	s example						
	CHARACTERISTICS			Connector dimension						
N	-Standard : Based on MIL-DTL-38999 Set-Shell Material: Aluminium-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastor-Contact Plating: Gold over cop-Durability: 500 Mating cy-Delivered with Souriau contacts and Action	c mer oper Alloy 0.8μm minimun /cles	m	DimNominalA34.9±0.3B19.07+0.1/-0.15R32.5MaxS31.8±0.4W2.2+0.9/-0.1VV THREADM15x1-6g		due to a use of the Specifications is (profession		nply with y a third party		2
	-Temperature Range: -65°C to +200-Salt Spray: 48 hours-Mass: 20.08 g ± 10%					9-2016 First Release ATE Latest modification Date:	- by	CUSTOMER DRAWING	MOD N°	-
					TITL	E	Aluminium Receptacle	e 8D series		
<u> </u>	SHELL TYPE : Jam nut Receptacle		F 22 B N		SCALE NA		General linear Tolerances: ±	NPRDS / PROJECT 859 This document is the prop	erty of	1
	CONTACT TYPE : Standard Crimp Con SHELL SIZE : 11	tact		ORIENTATIO CONTACT TYPE : SOCKET(500 Ma	SUUR	IAU WWW.S	OURIAU.COM	SOURIAU it must not be reproduce communicated without per		
	PLATING : F = Nickel			CONTACT LAYOUT :	: 11-22 FORMAT A3		SOURIAU DRG N° [±] 8D711F22BN-C		SHEET 1/2	
L	Н	G	F	E	D	C	B	A	-	

ſ	I	۵		m		0	Φ	A		
4		Contact Layout 22* 0 0 0 0 4#22D		Panel cutout JAM NUT RECEPTACLE (TYPE 7)						
ω	Ctc A B C D	11-22 X Y 1.905 1.905 1.905 -1.905 -1.905 -1.905 -1.905 1.905				Dim Nominal B 19.59+0/-0.3 ØC 20.96+0.25/	25		3	
N						due to a use of the Pro- the Specifications issued by		with nird party	2	
					A 30-09-2016 ISS DATE Designed By:	PN: 8D First Release Latest modification - by Date:	0711F22BN	M STOMER DRAWING	OD N°	
4					TITLE SCALE NA SOURIAU	Genera Tolera ±-	IAU.COM	NPRDS / PROJECT 859 This document is the property of SOURIAU it must not be reproduced or		
	Н	G	F	E	FORMAT A3 D		RIAU DRG N° 11F22BN-C B	communicated without permissi		