Г	т		Q		П			m	I	D		O
4		R 2.6 Max		✓ V Ihread →		S		ØA				
					Keving S	Shown as e	kample					
2	-Shell Plating -Insulator -Contacts -Seals & Grommet -Contact Plating	<ul> <li>Stainless Steel</li> <li>Passivated</li> <li>Thermoplastic</li> <li>Copper Alloy</li> <li>Silicon Elastome</li> <li>Gold over copp</li> </ul>	er er Alloy 0.8μm m	inimum	,			Nominal         34.9±0.3         19.07+0.1/-0.15         32.5Max         31.8±0.4         2.2+0.9/-0.1         M15x1-6g				SOURIAU sha due to a us the Specificatio (profes
	-Delivered without Sour -Temperature Range	: 500 Mating cyc iau contacts : -65°C to +200°( : 500 hours								ISS DA Designed By:	ATE	First Release Latest modifica Date
-	BASIC SERIES: SHELL TYPE : Jam nut R CONTACT TYPE : Stand SHELL SIZE : 11			11 K	01 S	B L	CONTAC	Delivered W ORIE CT TYPE : SOCKET(5	NTATION : B	SCALE NA SOURI	-[	
	PLATING : K = Pa	assivated						CONTACT LAY	OUT : 11-01	format A3		
L	Н		G		F			E	1	D		С

 $\forall$ 

	σ		Þ				
					4		
LAYOUT SHOWN AS EXA	MPLE				3		
all not be liable for any non-conformity or damage use of the Products which does not comply with ons issued by either of the Parties or by a third party essional recommendation, technical notice.) <u>Country</u> Jurisdiction & Control List FR Not Listed <b>PN: 8D711K01SBL</b>							
ation - by MOD N° te: CUSTOMER DRAWING							
Stainless Steel Receptacle 8D series         General linear Tolerances:       NPRDS / PROJECT         ±       859         V.SOURIAU.COM       This document is the property of SOURIAU it must not be reproduced or communicated without permission							
SOURIAU I 8D711K01			A	SHEET 1/2			

ſ	ت L	П	m		0		
	Contact Layout			٩ſ	Panel cutout		
4	01						4
	1#12				ØC		
ω	CtcXYA00				DimNominalB19.59+0/-0.25ØC20.96+0.25/-0		3
					SOURIAU shall not be liable for any non-c due to a use of the Products which doe the Specifications issued by either of the Pa	s not comply with	
23					(professional recommendation, teo Country FR	hnical notice.) Jurisdiction & Control List Not Listed	2
				A 30-09-2016 ISS DATE	PN: 8D711K01S First Release Latest modification - by	BL	 N°
				Designed By:     Date:     CUSTOMER DRAWING       TITLE     Stainless Steel Receptacle 8D series			
<b>→</b>					General linear Tolerances: ±	NPRDS / PROJECT 859 This document is the property of SOURIAU	1
				FORMAT A3	WWW.SOURIAU.COM SOURIAU DRO 8D711K01SB	it must not be reproduced or communicated without permission	
L	H G	F	E	D	C [		]