ſ	т		Q		п			т		D		O
4		R .6 Max					S	ØA				
					Keying	Shown a	as example					
	CHARACTERISTICS				-, 0				-			
	-Standard : Based on MIL	-DTL-38999 Serie	s III				Dim	r dimension Nominal				
2	-Shell Plating:-Insulator:-Contacts:-Seals & Grommet:-Contact Plating:-Durability:	500 Mating cycle	r Alloy 0.8µm mir es	nimum			A B R S W VV THREAD	34.9±0.3 19.07+0.1/-0.15 32.5Max 31.8±0.4 2.2+0.9/-0.1 M15x1-6g				SOURIAU shal due to a us the Specificatio (profes
	-Delivered with Souriau c -Temperature Range <u>:</u>	ontacts and Acce -65°C to +200°C									20.00.2016	First Dalassa
	-Salt Spray :	500 hours										First Release
										ISS Designe	DATE ed By:	Latest modifica Date
											TITLE	
	BASIC SERIES:	8D	7 - 1	L1 К	04 B	с				SCA	-	$= \bigcirc$
<b>_</b>	SHELL TYPE : Jam nut Re	-				L				N/		$\rightarrow$ $\checkmark$
	CONTACT TYPE : Standa	ard Crimp Contac	t				CONTA		NTATION : C	SO	URIAU	WWV
		ssivated					CONTAC	CT TYPE : SOCKET(5		FORM	1AT	
		ססועמוכט							001.11-04	A		
l	Н		G		F			E	1	D		С

 $\mathbf{\mathbf{n}}$ 

	σ		A				
					4		
LAYOUT SHOWN AS EXA	MPLE				3		
all not be liable for any non-conformity or damage use of the Products which does not comply with ons issued by either of the Parties or by a third party essional recommendation, technical notice.) <u>Country</u> Jurisdiction & Control List FR Not Listed PN: 8D711K04BC							
ation - by MOD te: <b>CUSTOMER DRAWING</b>							
Stainless Steel Receptacle 8D series         General linear       NPRDS / PROJECT         Tolerances:       859         ±       This document is the property of							
W.SOURIAU.CO		it must r	ment is the prop SOURIAU not be reproduc ated without per	ed or			
8D711K04		Δ	1/2				
l	В		A				

Г	T G	т (Г			
4	Contact Layout $ \begin{array}{c}  & & & \\  & & &$		Danel cutout JAM NUT RECEPTACLE (TYPE 7)	4	4
	(Insert arrangement 11-4)           Contact position ID         Contact location           A         +.065 (1.65)         +.065 (1.65)           B         +.065 (1.65)        065 (1.65)           C        065 (1.65)        065 (1.65)           D        065 (1.65)         +.065 (1.65)           Shell         Arrangement no.         Number of contacts         Size contacts         Service rating         Contact location           11         -4         4         20         I         All		ØC		_
ω			DimNominalB19.59+0/-0.25ØC20.96+0.25/-0	8	3
			SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party		
22			(professional recommendation, technical notice.)           Country         Jurisdiction & Control List           FR         Not Listed           PN: 8D711K04BC	2	2
			A       30-09-2016       First Release         ISS       DATE       Latest modification - by         Designed By:       Date:       CUSTOMER DRAWING	MOD N°	_
_ <b>_</b>			TITLE     Stainless Steel Receptacle 8D series       SCALE     General linear     NPRDS / PROJECT       NA     Tolerances:     859		1
			SOURIAU       WWW.SOURIAU.COM       This document is the propersource source source communicated without performance without performance source and source source communicated without performance source sou	ed or	
L	H G	FE	A3         8D711K04BC-C           D         C         B         A		