| ſ | T | ۵ | П | т | D | | C | | | |
|----------|---|-------------------------------------|--------|---|-------------|-------------------------------|--|--|--|--|
| 4 | R 22.6 Max | N Thread | | | | | LA | | | |
| | Keying Shown as example | | | | | | | | | |
| | -Durability : 500 Mating cyc | er er Alloy 0.8µm minimum les | | Connector dimension Dim Nominal A 34.9±0.3 B 19.07+0.1/-0.15 R 32.5Max S 31.8±0.4 W 2.2+0.9/-0.1 VV THREAD M15x1-6g | | | SOURIAU shall due to a use the Specification (profess | | | |
| | -Delivered with Souriau contacts and Acc -Temperature Range <u>:</u> -65°C to +200° -Salt Spray : 500 hours | | | | | 30-09-2016 DATE ned By: | First Release Latest modificat Date | | | |
| _ | BASIC SERIES: 8D SHELL TYPE : Jam nut Receptacle CONTACT TYPE : Standard Crimp Conta | | 01 P B | | NTATION : B | | - - - www | | | |
| | SHELL SIZE : 11 PLATING : S = Nickel | | | CONTACT TYPE : PIN(5 | OUT : 11-01 | MAT | | | | |
| | | T | | | | .3 | | | | |
| | н | G | F | E I | D | | С | | | |

| Ξ | A | | | | |
|---|-------------------------|--------------|---|--|--|
| | | | 4 | | |
| LAYOUT SHOWN AS EXAMPLE | | | 3 | | |
| all not be liable for any non-conformity or damage use of the Products which does not comply with ons issued by either of the Parties or by a third party essional recommendation, technical notice.) <u>Country</u> Jurisdiction & Control List FR Not Listed PN: 8D711S01PB | | | | | |
| ation - by MOD N° te: CUSTOMER DRAWING Stainless Steel Receptacle 8D series | | | | | |
| General linear NPRDS / PROJECT Tolerances: 859 ± This document is the property of SOURIAU W.SOURIAU.COM it must not be reproduced or | | | 1 | | |
| SOURIAU DRG N° 8D711S01PB-C | communicated without pe | SHEET 1/2 | | | |
| | - - | | | | |

| ſ | D I | т п | | | | | |
|----------|----------------|---|---|---|--|--|--|
| | Contact Layout | Panel cutout JAM NUT RECEPTACLE (TYPE 7) | | | | | |
| 4 | 01 | | | 4 | | | |
| | 1#12 | | | _ | | | |
| ω | CtcXYA00 | | Dim Nominal B 19.59+0/-0.25 ØC 20.96+0.25/-0 | 3 | | | |
| | | | SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) | | | | |
| N | | | | 2 | | | |
| | | | PN: 8D711S01PB A 30-09-2016 First Release | | | | |
| | | | ISS DATE Latest modification - by MOD N° Designed By: Date: CUSTOMER DRAWING | | | | |
| | | | TITLE Stainless Steel Receptacle 8D series | | | | |
| _ | | | SCALE General linear NPRDS / PROJECT NA Tolerances: ± 859 | 1 | | | |
| | | | SOURIAU This document is the property of SOURIAU It must not be reproduced or communicated without permission | | | | |
| | | | FORMAT SOURIAU DRG N° SHEET A3 8D711S01PB-C 2/2 | | | | |
| Ĺ | H G | FE | A3 8D711S01PB-C 2/2 D C B A | | | | |
| | | | \bigvee | | | | |