	T G T	m	D	0	B	_
4	R 22.6 Max () () () () () () () () () () () () () (S				4
	Keying S CHARACTERISTICS	Shown as example Connector dimension				
	-Standard : Based on WIL-DTL-38999 Series III-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy	Dim Nominal A 34.9±0.3 B 19.07+0.1/-0.15 R 32.5Max S 31.8±0.4 W 2.2+0.9/-0.1 VV THREAD M15x1-6g		SOURIAU shall not be liable for any nor due to a use of the Products which o the Specifications issued by either of the (professional recommendation,	does not comply with Parties or by a third party	
N	-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8μm minimum-Durability: 500 Mating cycles-Delivered with Souriau contacts and Accessories			PN: 8D711W0	Jurisdiction & Control List Not Listed	2
	-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours -Mass : 17.99 g ± 10%		ISS DATE	First Release Latest modification - by	MOD N°	_
			Designed By:	Date: Aluminium Re	customer drawing eceptacle 8D series	
	BASIC SERIES: 8D 7 - 11 W 04 A SHELL TYPE : Jam nut Receptacle Image: Section 10 and	В	SCALE -	General linear Tolerances: ±	NPRDS / PROJECT 859	1
	CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11	ORIENTATION : B CONTACT TYPE : PIN(500 Matings)	SOURIAU	WWW.SOURIAU.COM	This document is the property of SOURIAU it must not be reproduced or communicated without permission	
	PLATING : W = Olive drab Cadmium	CONTACT LAYOUT : 11-04	FORMAT A3	SOURIAU DI 8D711W04		
	H G F	E F	D	C	в і А	

Г	T	Q	П	m		0	Φ	A		
4	-X1 -X1 -X1 -X1 -X1 -X1 -X1 -X1	t Layout ★ +Y A + + + + + + + + + + + + + + + + + + +				Panel cutout JAM NUT RECEPTACLE (TYPE 7)	м Ф			4
	A +.065 B +.065 C 065 D 065 size no. Number of contacts cont	Contact location axis Y-axis (mm) (mm) (mm) (1.65) +.065 (1.65) (1.65) 065 (1.65) (1.65) +.065 (1.65) (1.65) +.065 (1.65) (1.65) +.065 (1.65) (1.65) +.065 (1.65) (1.65) +.065 (1.65) (1.65) +.065 (1.65) (1.65) +.065 (1.65) (1.65) +.065 (1.65) (1.65) +.065 (1.65) (1.65) +.065 (1.65) (1.65) +.065 (1.65) (1.65) +.065 (1.65)				Dim Nominal	25			
ω.						B 19.59+0/-0. ØC 20.96+0.25/				3
						the Specifications issued by	ducts which does not com either of the Parties or by nmendation, technical not	ply with a third party tice.)		
N						Country Jurisdiction & Control List FR Not Listed PN: 8D711W04AB				2
					A 01-10-201 ISS DATE	16 First Release			MOD N°	-
					Designed By:	Latest modification - by Date:		CUSTOMER DRAWING		
					TITLE	Alun	ninium Receptacle	8D series		
<u> </u>					SCALE NA SOURIAL	Genera Tolera ±	ances: 	NPRDS / PROJECT 859 This document is the prope SOURIAU		1
					FORMAT			it must not be reproduced communicated without perm		-
					A3		RIAU DRG N° 11W04AB-C		2/2	
L	Н	G	F	E	D	С	В	A		,