| | т <u>©</u> т | m | D | 0 | B | _ |
|---|--|---|---|------------------------------------|---|-----|
| 4 | R 22.6 Max b b b b b c c c c c c c c c c c c c c | S | | <image/> <image/> | <image/> | 4 |
| | Keying Sh | nown as example Connector dimension | | | | |
| | -Standard : Based on MIL-DTL-38999 Series III-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy | Dim Nominal A 34.9±0.3 B 19.07+0.1/-0.15 R 32.5Max S 31.8±0.4 W 2.2+0.9/-0.1 VV THREAD M15x1-6g | SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) | | | |
| N | -Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8μm minimum-Durability: 500 Mating cyclesDelivered with Coursies | | | PN: 8D711W0 | Jurisdiction & Control List Not Listed | 2 |
| | -Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +175°C -Salt Spray : 500 hours Mass | | A 01-10-2016 ISS DATE | | MOD N° | _ |
| | -Mass : 17.99 g ± 10% | | Designed By: | Date: | customer drawing eceptacle 8D series | _ |
| | BASIC SERIES: 8D 7 - 11 W 04 A SHELL TYPE : Jam nut Receptacle Image: Comparison of the second seco | D | SCALE -{ | General linear Tolerances: ± | NPRDS / PROJECT 859 | - 1 |
| | CONTACT TYPE : Standard Crimp Contact ORIENTATION : D SOURIAU WWW.SOURIAU.COM This document is the pro- SOURIAU | | This document is the property of SOURIAU it must not be reproduced or communicated without permission | | | |
| | PLATING : W = Olive drab Cadmium | CONTACT LAYOUT : 11-04 | FORMAT A3 | SOURIAU D 8D711W04 | | |
| | H G F | E F | D | C | в і А | |

| Г | D I | т (Г | | | | | |
|---|--|------|---|---|--|--|--|
| 4 | Contact Layout $\downarrow \qquad \qquad$ | | Panel cutout JAM NUT RECEPTACLE (TYPE 7) | 4 | | | |
| | Contact position ID Contact location X-axis Y-axis (mm) A +.065 (1.65) B +.065 (1.65) C 065 (1.65) C 065 (1.65) D 065 (1.65) C 065 (1.65) D 065 (1.65) Shell Arrangement no. Number of size Size no. Service contacts Contact rating 11 4 4 20 I All | | Dim Nomina | | | | |
| ω | | | B 19.59+0/-0 ØC 20.96+0.25 | | | | |
| | | | due to a use of the Pr the Specifications issued b | ble for any non-conformity or damage oducts which does not comply with y either of the Parties or by a third party ommendation, technical notice.) | | | |
| 0 | | | A 01-10-2016 First Release | FR Not Listed 2 0711W04AD | | | |
| | | | ISS DATE Latest modification - by | MOD N° | | | |
| | | | Designed By: Date: TITLE Alu | customer drawing minium Receptacle 8D series | | | |
| | | | NA Tole | ral linear NPRDS / PROJECT rances: 859 ± This document is the property of | | | |
| | | | SOURIAU WWW.SOUF | | | | |
| | | | | JRIAU DRG N°SHEET711W04AD-C2/2 | | | |
| L | H G | FE | | B A | | | |
| | | | | | | | |