	E G	т	m	D	0	Œ	A		1
4	R 22.6 Max () () () () () () () () () () () () () (	S			<image/> <image/>	OUT SHOWN AS EXAMPLE			4
		Keying Shown as ex	kample						
	CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium -Shell Plating : Olive drab Cadmium		Connector dimension           Dim         Nominal           A         34.9±0.3           B         19.07+0.1/-0.15           R         32.5Max			ot be liable for any non-conformi f the Products which does not co			
	-Insulator: Thermoplastic-Contacts: Copper Alloy		S         31.8±0.4           W         2.2+0.9/-0.1           V THREAD         M15x1-6g			ssued by either of the Parties or nal recommendation, technical r			
N	-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum					Country Juriso FR	liction & Control List Not Listed	]	2
	-Durability : 500 Mating cycles -Delivered without Souriau contacts				PN	: 8D711W04SBL			
	-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours			A 01-10-	2016 First Release				
	-Mass : 19.45 g ± 10%			ISS DAT Designed By:	TE Latest modification Date:	- by	CUSTOMER DRAWING	MOD N°	
				TITLE		Aluminium Receptac	le 8D series		
	BASIC SERIES: 8D 7 - 11 W	04 S B L		SCALE		General linear Tolerances:	NPRDS / PROJECT <b>859</b>		
<u> </u>	SHELL TYPE : Jam nut Receptacle         CONTACT TYPE : Standard Crimp Contact         SHELL SIZE : 11		Delivered W/O Cor ORIENTATIC CONTACT TYPE : SOCKET(500 Ma		AU WWW.S	± SOURIAU.COM	This document is the prop SOURIAU it must not be reproduc communicated without pe	ced or	1
	PLATING : W = Olive drab Cadmium		CONTACT LAYOUT :			SOURIAU DRG N° 8D711W04SBL-C		SHEET 1/2	
L	H G	F	E	D	С	B	A		J

Г	T G	т (П		
4	$\underbrace{\begin{array}{c} & & \\ & &$		DAM NUT RECEPTACLE (TYPE 7)	4
	Contact position ID         Contact location           A         +.065 (1.65)         +.065 (1.65)           B         +.065 (1.65)        065 (1.65)           C        065 (1.65)        065 (1.65)           D        065 (1.65)         +.065 (1.65)           Shell         Arrangement no.         Number of contacts         Size contacts         Service rating         Contact location           11         -4         4         20         I         All         MS20050-4		Dim Nominal	
ω			B 19.59+0/-0.25 ØC 20.96+0.25/-0	3
			SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)	
N			FR     Not Listed       A     01-10-2016   First Release	2
			ISS     DATE     Latest modification - by     M       Designed By:     Date:     CUSTOMER DRAWING       TITLE     Aluminium Receptacle 8D series	10D N°
<b>_</b>			SCALE       General linear       NPRDS / PROJECT         NA       Tolerances:       ±         SOURIAU       WWW.SOURIAU.COM       This document is the property of SOURIAU         it must not be reproduced or communicated without permission       it must not be reproduced or communicated without permission	
				SHEET 2/2
L	H G	F E	D C B A	