	T G T	m	D	0	B	_	
4	R 22.6 Max (p) (p) (p) (p) (p) (p) (p) (p) (p) (p)	S			<image/>	4	
	Keying Sh	own as example			VIPLE		
	CHARACTERISTICS Standard : Based on MIL-DTL-38999 Series III	Connector dimensionDimNominalA34.9±0.3					
	-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy	B 19.07+0.1/-0.15 R 32.5Max S 31.8±0.4 W 2.2+0.9/-0.1 VV THREAD M15x1-6g		SOURIAU shall not be liable for any no due to a use of the Products which the Specifications issued by either of th (professional recommendation	does not comply with e Parties or by a third party		
N	 -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles 	·		Country FR	Jurisdiction & Control List Not Listed	2	
	-Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +175°C -Salt Spray : 500 hours		A 01-10-2016	PN: 8D711W3	35PD		
_	-Mass : 17.68 g ± 10%		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING		
			TITLE	Aluminium Receptacle 8D series			
_	BASIC SERIES: 8D 7 - 11 W 35 P D SHELL TYPE : Jam nut Receptacle - - - 11 W 35 P D		SCALE -{	General linear Tolerances: ±	NPRDS / PROJECT 859	1	
	CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11	ORIENTATION : D CONTACT TYPE : PIN(500 Matings)	SOURIAU	WWW.SOURIAU.CO	M This document is the property of SOURIAU it must not be reproduced or communicated without permission		
	PLATING : W = Olive drab Cadmium	CONTACT LAYOUT : 11-35	format A3	SOURIAU D 8D711W35	ORG N° SHEET		
L	H G F	E	D	C	B A		

٢	Т	۵	т	m	D	0	Ψ]	
4	-8	Contact Layout $ \begin{array}{c} & & & & \\ & & & & \\ & & & & \\ & & & &$				Panel cutout	∧		4	
	Shell Arrangement N size no. c	Y-axis (mm) Contact position ID X-axis (mm) Y-axis (mm) +146 (3.71) 8 138 (3.51) 045 (1.14) +.118 (3.00) 9 138 (3.51) 045 (1.14) +045 (1.14) 10 085 (2.16) +.118 (3.00) -045 (1.14) 11 +.000 (0.00) +.056 (1.42) 118 (3.00) 12 +.049 (1.24) 035 (0.89) 146 (3.71) 13 049 (1.24) 035 (0.89) 118 (3.00) Applicable to MIL-DTL-38999 only) unber of Size Service contacts rating location Supersedes				ØC	∞ V			-
ى ت	11 -35	13 22D M Ali MS27526-35			E	Dim Nominal B 19.59+0/-0.25 ØC 20.96+0.25/-0			3	
	_									
						the Specifications issued by e	ucts which does not comply v	with ird party		
N								& Control List Listed	2	
						PN: 8D711W35PD				
					A 01-10-2016	First Release				
					ISS DATE	Latest modification - by			10D N°	_
					Designed By:	Date:	CUS	TOMER DRAWING		
					TITLE	Alumi	nium Receptacle 8) series		
					SCALE	General I Toleran		IPRDS / PROJECT		
→					NA			859 This document is the property	1	1
					SOURIAU	WWW.SOURI	AU.COM	SOURIAU it must not be reproduced or communicated without permiss		
					FORMAT	SOUR	IAU DRG N°		SHEET	
					A3		1W35PD-C		2/2	
	Н	G	F	I E	D	C	В	А		