	т G T	m	D	0	œ	A		,
CHARACTERISTICS Standard : Based on NUL-OTL-38999 Series II Shelf Material ::::::::::::::::::::::::::::::::::::	22.6 Max W Previous A Previous A Previ	S			EXAMPLE			4
- Shell Material : Aluminum - Shell Material : Aluminum - Shell Material : Bi 10270-12/0.15 - Shell Material : Southau shell not be liable for any non-conformity or damage - Contacts : Copper Alloy - Contact Size of performance : Southau shell not be liable for any non-conformity or damage - Contact Plating : Southau shell not be liable for any non-conformity or damage - Contact Plating : Southau shell not be liable for any non-conformity or damage - Contact Plating : Southau shell not be liable for any non-conformity or damage - Contact Plating : Southau shell not be liable for any non-conformity or damage - Contact Plating : Southau shell not be liable for any non-conformity or damage - Contact Plating : Southau shell not be liable for any non-conformity or damage - Contact Plating : Southau shell not be liable for any non-conformity or damage - Contact Plating : Southau shell not be liable for any non-conformity or damage - Contact Plating : Southau shell not be propriet of not not be prepoly of not not be propriet of not not be propriet of	CHARACTERISTICS	Connector dimension Dim Nominal						
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range : 65°C to +175°C -Salt Spray : 500 hours -Mass : 18.17 g ± 10% BASIC SERIES: 8D 7 11 Z 01 P C CONTACT TYPE : Statuard Crimp Contact 01 P SHELL SIZE : 11 ORIENTATION : C SOURIAU WWW.SOURIAU.COM This document is the property of sourmau incident without permission VEX.NELL SIZE : 11 CONTACT TYPE : PIN(500 Matings) CONTACT TYPE : PIN(500 Matings) Toild Accument is the property of sourmau incident without permission PLATING : Z = Black Zinc Nickel CONTACT TYPE : PIN(500 Matings) Toild Accument is the property of sourmau incident without permission	-Shell Plating: Black Zinc Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer	B 19.07+0.1/-0.15 R 32.5Max S 31.8±0.4 W 2.2+0.9/-0.1		due to a use of the Products w the Specifications issued by either o (professional recommenda Count	hich does not comply w of the Parties or by a th ation, technical notice.) ry Jurisdiction	with hird party & Control List		2
-Salt Spray : 500 hours -Mass : 18.17 g ± 10% -Mass : 18.17 g ± 10% 	-Delivered with Souriau contacts and Accessories				Z01PC			-
BASIC SERIES: 8D 7 - 11 Z 01 P C C SCALE Tolerances: 359 359 1 SHELL TYPE : Standard Crimp Contact ORIENTATION : C ORIENTATION : C NA SOURIAU This document is the property of sOURIAU SOURIAU it must not be reproduced or communicated without permission SHELL SIZE :11 CONTACT TYPE : Ellack Zinc Nickel CONTACT TYPE : PIN(500 Mattings) CONTACT LAYOUT : 11-01 SOURIAU It must not be reproduced or communicated without permission PLATING : Z = Black Zinc Nickel SHEET A3 SDURIAU DRG N° SHEET	-Salt Spray : 500 hours		ISS DATE	Latest modification - by	CUS	STOMER DRAWING	MOD N°	-
SHELL TYPE : Jam nut Receptacle NA Tolerances: 859 CONTACT TYPE : Standard Crimp Contact ORIENTATION : C SOURIAU SOURIAU This document is the property of SOURIAU.COM SOURIAU SHELL SIZE : 11 CONTACT TYPE : PIN(500 Matings) CONTACT TYPE : PIN(500 Matings) FORMAT SOURIAU DRG N° SHEET PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 11-01 FORMAT SOURIAU DRG N° SHEET 1 1 1 1 1 1	BASIC SERIES: 8D 7 - 11 Z 01 P	c		General linear				
A3 SOORIAO DRG N 1/2	SHELL TYPE : Jam nut Receptacle CONTACT TYPE : Standard Crimp Contact				СОМ	This document is the proper SOURIAU it must not be reproduced	lor	1
	PLATING : Z = Black Zinc Nickel	CONTACT LAYOUT : 11-0				Δ		

	т	D	П	п		0	₽ ₽	•
	Contact Layout Panel cutout							
4	(01 ~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~				AM NUT RECEPTACLE (TYPE 7)		4
ω	Ctc A		Y 0			Dim Nominal B 19.59+0/-0.25 ØC 20.96+0.25/-0		3
						SOURIAU shall not be liable for any not due to a use of the Products which the Specifications issued by either of th (professional recommendation)	n does not comply with e Parties or by a third party	
N						Country FR	Jurisdiction & Control List Not Listed	2
						PN: 8D711Z0)1PC	
					A 01-10-2016			
_					ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°
					TITLE	Aluminium F	Receptacle 8D series	
_					SCALE -[General linear Tolerances:	NPRDS / PROJECT 859	1
					SOURIAU		This document is the p SOURIAU it must not be reprod communicated without	duced or
					FORMAT A3	SOURIAU D	DRG N°	SHEET
Ĺ	Н	G	F	E		8D711Z01	B A	2/2