ſ	т		G		П			т		D		O	
4	B Du flat	R 2.6 Max		 VV Thread 				ØA					
					Keying	Shown as	example						
2	CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III -Shell Material : Stainless Steel -Shell Plating : Passivated -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			ninimum			Connector Dim A B R S W VV THREAD	r dimension Nominal 38.1±0.3 23.82+0.1/-0.15 32.5Max 34.9±0.4 2.2+0.9/-0.1 M18x1-6g				SOURIAU sh due to a u the Specificati (profe	
		 -65°C to +200° 500 hours 	°C							ISS	DATE	First Release Latest modifica	
										Designe	ed By: TITLE	Date	
→	BASIC SERIES: SHELL TYPE : Jam nut F	-		13 K	04 P	с				SCA NA	A -		
	CONTACT TYPE : Stan	idard Crimp Cont	аст				COI	ORIE	NTATION : C	SO	URIAU	WWV	
		assivated						CONTACT LAY		FORM			
		I								A	3		
	Н		G		F			E		D		С	

 \forall

	Φ		А				
					4		
LAYOUT SHOWN AS EXA	MPLE				3		
all not be liable for any non-conformity or damage use of the Products which does not comply with ons issued by either of the Parties or by a third party essional recommendation, technical notice.) <u>Country</u> Jurisdiction & Control List FR Not Listed PN: 8D713K04PC							
ation - by MOD N° te: CUSTOMER DRAWING Stainless Steel Receptacle 8D series							
General linear NPRDS / PROJECT Tolerances: 859 ± This document is the property of							
W.SOURIAU.CC SOURIAU E 8D713K04	DRG N°		SOURIAU ust not be reprodu inicated without p				
I	U	I	A				

ſ	T G	п	ш	D	0	σ	Þ		-
Contact Layout $ \begin{array}{c} & & \\$									4
	Contacts (Insert arrangement 13-4) Location Contact position ID Y-axis position ID A +.000 (0.00) +.150 (3.81) B +.146 (3.71) +.035 (0.89) C +.000 (0.00) 083 (2.11) D 146 (3.71) +.035 (0.89) C +.003 (0.20) Stell Arrangement Number of Size Service Contact Supersedes								
ω	Size no. contacts contacts rating location 13 -4 4 16 I All MS20051-4				Dim Nominal B 24.26+0/-0.2 ØC 25.65+0.25/				3
					SOURIAU shall not be liabl due to a use of the Proc the Specifications issued by (professional recom	ducts which does not co	mply with oy a third party		
N							iction & Control List Not Listed		2
				A 28-09-2016 ISS DATE Designed By:	Latest modification - by Date:		CUSTOMER DRAWING	MOD N°	
<u> </u>				SCALE NA SOURIAU	Stainle General Tolera ±- WWW.SOURI	nces: -	ICLE 8D SERIES NPRDS / PROJECT 859 This document is the prop SOURIAU it must not be reproduc communicated without pe	ed or	1
	H G I	F	E	FORMAT A3 D		RIAU DRG N° 13K04PC-C B	A	SHEET 2/2	_