| ſ | Т | | G | | П | | | т | | D | | 0 |
|----------|---|--|--|-----------|--------|-------------|---|---|---|-----------|------------|--|
| 4 | B On flat | R 22.6 Max | | VV Thread | | | | ØA | | | | |
| | | | | | Keying | Shown as ex | ample | | | | | |
| S | CHARACTERISTICS -Standard : Based on N -Shell Material -Shell Plating -Insulator -Contacts -Seals & Grommet -Contact Plating -Durability -Delivered without So -Temperature Range -Salt Spray | Stainless Stee Nickel Thermoplastic Copper Alloy Silicon Elastor Gold over cop 500 Mating cy uriau contacts | l c mer oper Alloy 0.8μm γcles | minimum | | | Connector Dim A B R S W V THREAD | Nominal 38.1±0.3 23.82+0.1/-0.15 32.5Max 34.9±0.4 2.2+0.9/-0.1 M18x1-6g | | | 28-09-2016 | SOURIAU sha due to a us the Specificatio (profes First Release |
| | -Salt Spray | : 500 hours | | | | | | | | ISS | DATE | Latest modifica |
| | | | | | | | | | | Designe | TITLE | Date |
| _ | BASIC SERIES: SHELL TYPE : Jam nut CONTACT TYPE : Sta SHELL SIZE : 13 | t Receptacle | BD 7 - | 13 S | 03 S | EL | CONTAC | | /O Contacts NTATION : E 00 Matings) | SCA NA | 4 | - - wwv |
| | PLATING : S = | Nickel | | | | | | CONTACT LAY | OUT : 13-03 | FORM | | 1 |
| L | Н | | G | | F | | | E | 1 | D | - | С |

 \forall

| | σ | | : | Þ | | | | |
|--|------|--|---|---|--|---|--|--|
| | | | | | | 4 | | |
| LAYOUT SHOWN AS EXA | MPLE | | | | | 3 | | |
| all not be liable for any non-conformity or damage use of the Products which does not comply with ons issued by either of the Parties or by a third party essional recommendation, technical notice.) <u>Country</u> Jurisdiction & Control List FR Not Listed PN: 8D713S03SEL | | | | | | | | |
| ation - by MOD N° te: CUSTOMER DRAWING | | | | | | | | |
| Stainless Steel Receptacle 8D series General linear NPRDS / PROJECT Tolerances: 859 ± This document is the property of | | | | | | | | |
| SOURIAU.COM SOURIAU it must not be reproduced or communicated without permission SOURIAU DRG N° SHEET 8D713S03SEL-C 1/2 | | | | | | | | |
| B A | | | | | | | | |

| | D I | П | m | | 0 | | _ |
|----------|--|---|---|---|---|--|---|
| 4 | Contact Layout 03 | | | | Panel cutout | | 4 |
| ∠ | 13-03 Ctc X Y A 2.39 1.47 B 0 -2.79 C -2.39 1.47 | | | | Dim Nominal B 24.26+0/-0.25 ØC 25.65+0.25/-0 | | 3 |
| | | | | | SOURIAU shall not be liable for any non-co due to a use of the Products which doe the Specifications issued by either of the Par (professional recommendation, tec Country FR PN: 8D713S03S | s not comply with rties or by a third party hnical notice.) Jurisdiction & Control List Not Listed | 2 |
| | | | | A 28-09-2016 ISS DATE Designed By: TITLE | First Release Latest modification - by Date: Stainless Steel Re | MOD N° CUSTOMER DRAWING ceptacle 8D series | |
| <u> </u> | | | | SCALE NA SOURIAU | General linear Tolerances: ± | NPRDS / PROJECT 859 This document is the property of SOURIAU it must not be reproduced or communicated without permission | 1 |
| | H G | F | E | FORMAT A3 D | SOURIAU DRO 8D713S03SE C E | L-C 2/2 | |