ſ	Т	۵		п	п		D	0
4		R Max W O O O O O O O O O O O O O O O O O O	VV Thread			ØA		
				Keying Shown as	example			
N	CHARACTERISTICS     -Standard : Based on MIL-DTL-38999 Series III     -Shell Material   : Stainless Steel     -Shell Material   : Stainless Steel     -Shell Plating   : Nickel     -Insulator   : Thermoplastic     -Contacts   : Copper Alloy     -Seals & Grommet   : Silicon Elastomer     -Contact Plating   : Gold over copper Alloy 0.8µm minimum     -Durability   : 500 Mating cycles     -Delivered with Souriau contacts and Accessories     -Temperature Range   : -65°C to +200°C     -Salt Spray   : 500 hours				Nominal       38.1±0.3       82+0.1/-0.15       32.5Max       34.9±0.4       2.2+0.9/-0.1	A 28-09-20	SOURIAU shall due to a use the Specification (profess 016 First Release	
							ISS DATE Designed By:	Latest modificat
_	BASIC SERIES: SHELL TYPE : Jam nut Rece	8D 7 -	13 S 04	B D			TITLE SCALE NA	the Specification (profess) 3-09-2016 First Release DATE Latest modificati 3y: Date: TLE RIAU WWW
	CONTACT TYPE : Standar	d Crimp Contact				ORIENTATION	—   SUURIA	U www
	SHELL SIZE : 13					PE : SOCKET(500 Matin		
	PLATING : S = Nicke	21				CONTACT LAYOUT : 13	<u>-04</u> A3	
l	Н	G		F	E		D	С

	σ		2	۵			
						4	
LAYOUT SHOWN AS EXAM	IPLE					3	
all not be liable for any non-conformity or damage use of the Products which does not comply with ons issued by either of the Parties or by a third party essional recommendation, technical notice.) <u>Country</u> Jurisdiction & Control List <u>FR</u> Not Listed PN: 8D713S04BD							
ation - by MOD N° te: CUSTOMER DRAWING Stainless Steel Receptacle 8D series							
General linear NPRDS / PROJECT   Tolerances: 859					of	1	
W.SOURIAU.COM   This document is the property of SOURIAU     it must not be reproduced or communicated without permission     SOURIAU DRG N°   SHEET							
8D713S04				1/2			
BA							

Г	D D	)	m	D	0	Ξ	A		,
4	Contact Layout x y y y y y y y y			MAL	Panel cutout				4
	Contact position ID     X-axis (mm)     Y-axis (mm)       A     +.000 (0.00)     +.150 (3.81)       B     +.146 (3.71)     +.035 (0.89)       C     +.000 (0.00)    083 (2.11)       D    146 (3.71)     +.035 (0.89)       Shell     Arrangement no.     Number of contacts     Size contacts     Service rating       13     -4     4     16     I	) )) ) Contact Supersedes location			Dim Nominal	1			
ω					B     24.26+0/-0.25       ØC     25.65+0.25/-0				3
	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)								
N					PN: 8D71	FR N	ion & Control List Not Listed		2
					Latest modification - by			MOD N°	-
		Designed By: Date: CUSTOMER DRAWING   TITLE Stainless Steel Receptacle 8D series							
<u> </u>				SCALE	General line Tolerances ±		NPRDS / PROJECT <b>859</b>		1
				SOURIAU	SOURIAU   WWW.SOURIAU.COM   This document is the property of SOURIAU     it must not be reproduced or communicated without permission				
				FORMAT A3		AU DRG N° 3S04BD-C		SHEET 2/2	
L	H G	F	E	D	C 00713	B	A		J