ſ	т	Q	нт –	п			0
4	22.6 M		V Thread	S	ØA		LA
			Keying S	Shown as example			
	-Shell Plating: Nick-Insulator: Ther-Contacts: Copp-Seals & Grommet: Silico-Contact Plating: Gold	less Steel	iinimum	R S	nension Nominal 38.1±0.3 3.82+0.1/-0.15 32.5Max 34.9±0.4 2.2+0.9/-0.1 M18x1-6g		SOURIAU shall due to a use the Specification (profess
	-Delivered with Souriau conta -Temperature Range <u>:</u> -65° -Salt Spray : 500	C to +200°C				A 28-09-2016 ISS DATE Designed By: TITLE	First Release Latest modificat
_	BASIC SERIES: SHELL TYPE : Jam nut Recepta CONTACT TYPE : Standard C SHELL SIZE : 13	acle	13 S 04 S	B CONTACT TY	ORIENTATION : I YPE : SOCKET(500 Matings	SCALE NA B SOURIAU	www.
	PLATING : S = Nickel				CONTACT LAYOUT : 13-0	4 FORMAT	
	,		•		7	- A3	
	Н	G	F	E	\mathbf{V}	D	С

	ω		A			
					4	
LAYOUT SHOWN AS EXAMPLE						
all not be liable for any non-conformity or damage use of the Products which does not comply with ons issued by either of the Parties or by a third party essional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed PN: 8D713S04SB						
ation - by te:			ER DRAWING	MOD N°	- - -	
Stainless Steel General linear Tolerances: ±	NPRDS	1				
W.SOURIAU.COM SOURIAU DI 8D713S04		SOURIAU ust not be reprodu inicated without p				
I	В	I				

Г	T G	П	т	D B A
4	$\begin{array}{c} & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ \hline \\ & & & \\ & & & \\ \hline \\ & & & \\ & & & \\ \hline \\ \\ & & & \\ \hline \\ & & & \\ \hline \\ & & \\ \hline \\ \\ & & \\ \hline \\ \\ & & \\ \hline \\ \\ \\ \hline \\ \\ \hline \\ \hline \\ \\ \hline \\ \hline \\ \\ \hline \\ \\ \hline \\ \hline \\ \\ \hline \\ \hline \\ \hline \\ \hline \\ \\ \hline \\ \hline \\ \\ \hline \\ \hline \\ \hline \\ \\ \hline \\ \hline \\ \hline \\ \\ \hline \\ \hline \\ \\ \hline \\ \hline \\ \hline \\ \hline \\ \\ \hline \\ \hline \\ \hline \\ \hline \\ \\ \hline \\ \\ \hline \\$			Panel cutout JAM NUT RECEPTACLE (TYPE 7)
	Contact position ID X-axis (mm) Y-axis (mm) A +.000 (0.00) +.150 (3.81) B +.146 (3.71) +.035 (0.89) C +.000 (0.00) 083 (2.11) D 146 (3.71) +.035 (0.89) Shell Arrangement no. Number of contacts Size contacts Service rating Contact location Supersed 13 -4 4 16 I All MS20051			Dim Nominal
ω				B 24.26+0/-0.25 ØC 25.65+0.25/-0 3
				SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)
S				Country Jurisdiction & Control List FR Not Listed PN: 8D713S04SB
_				A 28-09-2016 First Release ISS DATE Latest modification - by
				Designed By: Date: CUSTOMER DRAWING TITLE Stainless Steel Receptacle 8D series
_				SCALE General linear NPRDS / PROJECT NA Image: Description of the second
				SOURIAU This document is the property of SOURIAU it must not be reproduced or communicated without permission
				FORMATSOURIAU DRG N°SHEETA38D713S04SB-C2/2
L	H G	F	E	D C B A