	۲ G	П	m		C	σ	A		
4	R 22.6 Max () () () () () () () () () () () () () (N Thread	S			AS EXAMPLE			4
		Keying Shown a	as example						
	CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm		Connector dimension Dim Nominal A 38.1±0.3 B 23.82+0.1/-0.15 R 32.5Max S 34.9±0.4 W 2.2+0.9/-0.1 VV THREAD M18x1-6g			er of the Parties or by a th ndation, technical notice. untry Jurisdiction	with hird party		2
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories				PN: 8D71	.3W04SD			
_	-Temperature Range: -65°C to +175°C-Salt Spray: 500 hours-Mass: 27.92 g ± 10%			A 29-09-2016 ISS DATE Designed By:	First Release Latest modification - by Date:	CUS	STOMER DRAWING	MOD N°	
				TITLE	Alumin	ium Receptacle 8[) series		
_	BASIC SERIES:8D7SHELL TYPE : Jam nut ReceptacleCONTACT TYPE : Standard Crimp ContactSHELL SIZE : 13	13 W 04 S D	ORIENTATION CONTACT TYPE : SOCKET(500 Matin		General line Tolerance ± WWW.SOURIA	J.COM	IPRDS / PROJECT 859 This document is the prope SOURIAU it must not be reproduce communicated without peri	ed or	1
	PLATING : W = Olive drab Cadmium		CONTACT LAYOUT : 13-			AU DRG N° W04SD-C		SHEET 1/2	
L	H G	F	E	D	C	B	A		J

Г	D I	т (Г		B			
	Contact Layout		Panel cutout JAM NUT RECEPTACLE (TYPE 7)				
4	$-\mathbf{x} \begin{pmatrix} \mathbf{b} \\ \mathbf{b} \\ \mathbf{b} \\ \mathbf{b} \\ \mathbf{c} \\$			N N	4		
	Contacts Contacts Location X-axis (mm) (mm) A +.000 (0.00) +.150 (3.81) B +.146 (3.71) +.035 (0.89) C +.000 (0.00) 146 (3.71) +.035 (0.89)						
	Shell sizeArrangement no.Number of contactsSize 						
ω			Dim Nomir B 24.26+0/ ØC 25.65+0.3	-0.25	3		
			due to a use of the F the Specifications issued	able for any non-conformity or damage Products which does not comply with by either of the Parties or by a third party commendation, technical notice.)			
2				CountryJurisdiction & Control ListFRNot Listed	2		
				PN: 8D713W04SD			
			A 29-09-2016 First Release				
_			ISSDATELatest modification - byDesigned By:Date:	CUSTOMER DRAWING	OD N°		
			TITLE Alu	TITLE Aluminium Receptacle 8D series			
_				eral linear NPRDS / PROJECT lerances: 859	1		
			SOURIAU WWW.SOU	SOURIAU This document is the property of SOURIAU it must not be reproduced or communicated without permission			
					HEET		
L					2/2		
	H G I	F I E	D C	B A			