

т <u>О</u> т	m		
R 22.6 Max () () () () () () () () () () () () ()	S	Image: Application of the second se	
Κονί	ng Shown as example		
CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum -Durability : 500 Mating cycles -Delivered without Souriau contacts -Temperature Range : -65°C to +175°C	Connector dimension Dim Nominal A 44.5±0.3 B 30.15+0.1/-0.15 R 32.5Max S 41.3±0.4 W 2.2+0.9/-0.1 VV THREAD M25x1-6g	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)	
-Salt Spray : 500 hours		ISS DATE Latest modification - by	MO
		Designed By: Date: CUSTOMER DRAWING TITLE Aluminium Receptacle 8D series	
BASIC SERIES: 8D 7 - 17 Z 20 S SHELL TYPE : Jam nut Receptacle	N L Delivered W/O Contacts	SCALE SCALE	
CONTACT TYPE : Standard Crimp Contact	ORIENTATION : N	- SOURIAU WWW.SOURIAU.COW it must not be reproduce	
SHELL SIZE : 17 PLATING : Z = Black Zinc Nickel	CONTACT TYPE : SOCKET(500 Matings) CONTACT LAYOUT : 17-20	s) communicated without per 0 FORMAT SOURIAU DRG N°	
		A3 8D717Z20SNL-C	1/

	I	Q	П	П		0	Φ		_
	Contac	t Layout				Danal sutout			
						Panel cutout			
	2	0*				JAM NUT RECEPTACLE (TYPE 7)			
4									4
		±12 22D							
	17	-20					¥		
		х ү				Ør			
	A	0 5.51				K>			
	B 3	.17 0							
		0 -5.51				Dim Nominal			
ω		.17 0				B 30.73+0/-0.2 ØC 32.01+0.25/			3
		.16 7.06				pc 52.01.0.23/			
		.29 4.29							
		.11 4.03							
		05 1.4							
		.05 -1.4 .11 -4.03							
		.29 -4.29				SOURIAU shall not be liab	le for any non-conformity	v or damage	
		.16 -7.06					ducts which does not con		
		.16 -7.06				the Specifications issued by	either of the Parties or by	y a third party	
		.29 -4.29				(professional recom	nmendation, technical no	tice.)	
	11 -7	.11 -4.03					Country Jurisdic	ction & Control List	
N	12 -8	.05 -1.4						Not Listed	2
	13 -8	.05 1.4							
	14 -7	4.03				PN: 8D	717Z20SNL		
		.29 4.29							_
	16 -4	.16 7.06			A 01-10-20	016 First Release			
					ISS DATE	E Latest modification - by		MOD N°	•
					Designed By:	Date:		CUSTOMER DRAWING	
					TITLE	Alum	ninium Receptacle	tacle 8D series	
					SCALE	Genera	al linear	NPRDS / PROJECT	_
<u> </u>					NA	Tolera ±	ances:	859	1
					SOURIA	WWW.SOUR	IAU.COM	This document is the property of SOURIAU it must not be reproduced or communicated without permission	
					FORMAT	SOUI	RIAU DRG N°	SHEET	\neg
					A3		17Z20SNL-C	2/2	
	Н	G		E	D	C	B	l	