

| _ | T Q T | m | | 0 | Φ | A | | _ | | | | |
|----------|---|--|--------------|--|---|---|--------|---|--|--|--|--|
| 4 3 | R Image: Constrained of the second of th | | | | | | | | | | | |
| 2 | CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum -Durability : 500 Mating cycles -Delivered without Souriur contacts -Temperature Range : -65°C to +175°C -Salt Spray : 500 hours | Shown as example | Designed By: | F PN: 8D717 First Release Latest modification - by Date: | which does not comply r of the Parties or by a t dation, technical notice intry Jurisdictio R NC 7Z22SDL | v with chird party .) n & Control List ot Listed STOMER DRAWING | MOD N° | 2 | | | | |
| _ | BASIC SERIES: 8D 7 - 17 Z 22 S SHELL TYPE : Jam nut Receptacle | D L Delivered W/O Contacts ORIENTATION : D CONTACT TYPE : SOCKET(500 Matings) CONTACT LAYOUT : 17-22 | SOURIAU | General linea Tolerances: ± WWW.SOURIAU SOURIA | .COM | D series NPRDS / PROJECT 859 This document is the prope SOURIAU it must not be reproduced communicated without perm | d or | 1 | | | | |

| Г | т | | 0 |) (| П | т | | | 0 | ω | | Þ | |
|--------|---|--------|--------------------|-----------|---|---|---|--------------|---|-------------------------|---|--------------------|---|
| | | | Contact Layout | | | | | | Panel cutout | | | | |
| | | | 22 | | | | | | JAM NUT RECEPTACLE (TYPE 7) | | | | |
| 4 | | | | | | | | | | ∧ | | | 4 |
| | | | 2#12 2#8 Triax | | | | | | | | | | |
| | | | 2#0 IIIdx 17-22 | | | | | | | <u> </u> | | | |
| | | Ctc | X | Y | | | | | < ØC > | | | | |
| | | A B | 0 6.32 | 4.57 0 | | | | | | | | | |
| | | С | 0 | -4.57 | | | | _ | Dim Nominal B 30.73+0/-0.25 | <u>;</u> | | | |
| ယ | | D | -6.32 | 0 | | | | | ØC 32.01+0.25/-0 |) | | | 3 |
| | | | | | | | | | | | | | |
| | L | | | | | | | [| | | | | |
| | | | | | | | | | SOURIAU shall not be liable due to a use of the Produ the Specifications issued by ei (professional recomn | ucts which does not cor | nply with y a third party | | |
| \sim | | | | | | | | | | Country Jurisdi FR | ction & Control List Not Listed | | 2 |
| | | | | | | | | | PN: 8D7 | 17Z22SDL | | | |
| | | | | | | | | A 01-10-2016 | First Release | | | | _ |
| | | | | | | | | ISS DATE | Latest modification - by | | | MOD N° | |
| | | | | | | | | Designed By: | Date: | | CUSTOMER DRAW | ING | _ |
| | | | | | | | | TITLE | Alumi | nium Receptacl | e 8D series | | |
| _ | | | | | | | | SCALE - | General li Tolerand ± | | NPRDS / PROJEC 859 | Т | 1 |
| | | | | | | | | SOURIAU | WWW.SOURIA | AU.COM | This document is t SOURI it must not be re communicated witl | AU eproduced or | |
| | | | | | | | | FORMAT | SOUR | IAU DRG N° | | SHEET | _ |
| | | | | | | | 7 | A3 | | 7Z22SDL-C | | 2/2 | |
| | Н | | (| | F | E | | D | C | В | | А | |