ſ	ם T		т			т		D		0
4	R 22.6 Max H H H H H H H H H H H H H H H H H H H	V Thread				ØA				
			Key	ying Shown as	example					
	CHARACTERISTICS-Standard : Based on MIL-DTL-38999 Series III-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer				Connector Dim A B R S W VV THREAD	Nominal 49.2±0.3 33.32+0.1/-0.15 32.5Max 46±0.4 3+0.9/-0.1 M28x1-6g				SOURIAU sha due to a us the Specificatio (profes
S	-Contact Plating: Gold over copper Alloy (-Durability: 500 Mating cycles-Delivered with Souriau contacts and Accessories-Temperature Range: -65°C to +175°C-Salt Spray: 500 hours	D.8μm minimum						A	30-09-2016	First Release
								ISS Design	DATE ed By: TITLE	Latest modifica Date
_	BASIC SERIES:8D7SHELL TYPE: Jam nut ReceptacleCONTACT TYPE: Standard Crimp Contact	- 19 W	28	S N			NTATION : N	SCA N/	م -[$\Box \oplus$
	SHELL SIZE : 19				CONTAC	T TYPE : SOCKET(5		SO	URIAU	WWV
	PLATING : W = Olive drab Cadmium					CONTACT LAY		FORM		

F

Е

Н

G

С

D

>	B						
LAYOUT SHOWN AS EXAMPLE							
shall not be liable for any non-conformity or damage a use of the Products which does not comply with ations issued by either of the Parties or by a third party ofessional recommendation, technical notice.) $\frac{Country \qquad Jurisdiction \& Control List \\ \hline FR \qquad Not Listed}$ PN: 8D719W28SN							
ification - by MOD N° Date: CUSTOMER DRAWING							
Aluminium Receptacle 8D series							
Toler	al linear ances: :	859					
VW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission							
	RIAU DRG N° 19W28SN-C		SHEET 1/2				
B A							

ſ	т	Q	нт — — — — — — — — — — — — — — — — — — —	п		0			-
4		Contact Layout				Panel cutout JAM NUT RECEPTACLE (TYPE 7)			4
	Contact position ID (mm)	$\begin{array}{c c} & & & & \\ & & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & & \\ & & &$							
ω	A +.066 (1.88) B +.189 (4.80) C +.286 (7.26) D +.345 (8.76) E +.357 (9.07) F +.321 (8.15) G +.242 (6.15) H +.130 (3.30) J +.000 (0.000) K 130 (3.30) L 242 (6.15) M 327 (9.07) P 345 (8.76) Shell Arrangement	$\begin{array}{rrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrr$			Ē	Dim Nominal B 33.91+0/-0.25 ØC 35.18+0.25/-0			3
	F				[
						SOURIAU shall not be liable for any non-o due to a use of the Products which doo the Specifications issued by either of the Pa (professional recommendation, tee	es not comply with arties or by a third party		
N						CountryJurisdiction & Control ListFRNot Listed			2
						PN: 8D719W28SN			
					A 30-09-2016 First Release				
					ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	
				TITLE Aluminium Receptacle 8D series					
-					SCALE NA SOURIAU	General linear Tolerances: ± WWW.SOURIAU.COM	NPRDS / PROJECT 859 This document is the prop SOURIAU it must not be reproduce		1
					FORMAT A3	SOURIAU DR 8D719W28S	communicated without pe		-
L	Н	G	F	E	D		B A		1