

					1				
	ω	I	A						
		I]				
4	m				4				
	11-				4				
	1 16	1							
		1							
		1							
S EXA	AMPLE				3				
any	non-conformit	ty or damage							
s which does not comply with									
er of the Parties or by a third party ndation, technical notice.)									
untry FR	Jurisd	liction & Con Not Listed	trol List		2				
]	2				
1S4	41BC								
				MOD N°					
		CUSTOME	R DRAWING						
Stor	el Recepta	ادام ۲۵ دم	ories						
JIE	Li Necepia		.1153						
ar	NPRDS / PROJECT								
:		859							
	1	This do	cument is the prop	perty of					
I.COM SOURIAU it must not be reproduced or									
		commun	icated without pe						
	DRG N°			SHEET					
.S4	1BC-C			1/2	J				
	В		А						

ſ	<u>т</u>	۵	П	т		0	
		Contact Layout				Panel cutout	
						JAM NUT RECEPTACLE (TYPE 7)	
4	<	31° 23 31° 23 31° 23 31° 24 10° 20 HOLES 10° 20 HOLES 10° 20 HOLES 10° 20 HOLES 10° 20 HOLES					
						Max. thickness panel for receptacle:Type 7: 3.2 mm	
ω	Shell Arrangement Numi: size no. cont	Insert arrangement 21-41 ber of Size Service Contact Supersedes acts contacts rating location	-			Dim Nominal B 37.08+0/-0.25	
	21 -41 4	1 20 I Ali MS20055-41]			ØC 38.35+0.25/-0	
						SOURIAU shall not be liable for any due to a use of the Products whi the Specifications issued by either of (professional recommendation)	
2						Country	
						FR PN: 8D721S	
					A 08-11	-2016 First Release	
					ISS DA Designed By:	TE Latest modification - by Date:	
					TITLE	Stainless Ste	
_					SCALE	General linear Tolerances:	
					SOURI	SOURIAU WWW.SOURIAU.CO	
					FORMAT A3	SOURIAU 8D721S4	
l	Н	G	F	E	D	8D72134	
			•	-	V	· · · ·	

