

	ω		A						
	10/				4				
	1/1								
	A second se								
	a la	1							
S EXA	MPLE				3				
2014 0	on-conformit	w or damage							
whick	any non-conformity or damage which does not comply with								
	r of the Parties or by a third party dation, technical notice.)								
intry R									
TVV	41SE								
		CUSTOMER	RDRAWING	MOD N°					
um F	m Receptacle 8D series								
ar									
		NPRDS / PROJECT 859							
COM This document is the property of SOURIAU it must not be reproduced or									
		it must not be reproduced or communicated without permission							
	DRG N° 1SE-C			SHEET 1/2					
vv4	B		A	-, -	J				

1	ш	Q	н г	т		•
		Contact Layout				Panel cutout
						JAM NUT RECEPTACLE (TYPE 7)
4	<	31° 23' 27° 41' - 13 HOLES 10° - 20 HOLES				
						Max. thickness panel for receptacle:Type 7: 3.2 mm
	Shell Arrangement Numb	Insert arrangement 21-41 ber of Size Service Contact Supersedes	1			Dim Nominal B 37.08+0/-0.25
ယ	size no. conta 21 -41 4:					ØC 38.35+0.25/-0
2						SOURIAU shall not be liable for an due to a use of the Products wi the Specifications issued by either o (professional recommenda Count FR PN: 8D721
					ISS DA	-2016 First Release TE Latest modification - by
					Designed By:	Date:
					TITLE	Aluminiun
<u> </u>					SCALE NA	General linear Tolerances:
					SOURI	AU WWW.SOURIAU.C
					FORMAT	SOURIAU
		1	1		A3	8D721W
	Н	G	F	E	D	C

