
Railway Interconnect Solutions





SOURIAU

CLOSED ELECTRICAL OPERATING AREAS

SOURIAU has developed a dedicated range of ruggedized and reliable connectors for the railway market, fully compliant with railway standards, RoHS and fire smoke certified. SOURIAU is always committed to providing quality products and to support their customers with customized solutions.

Quality and customer support is our first goal






MSG 3U Series

SOURIAU's Connectors on Railway Equipment

- 1. Closed electrical operating areas
- 2. Cabin and interiors
- 3. Closed electrical operating areas with forced filtered ventilation
- 4. Outdoor static applications
- 5. Outdoor dynamic applications
- 6. Outdoor highly dynamic applications





MB 29/44/52 contacts #16 Reinforced shielding Secure lever locking 500 matings/unmatings



1. Closed Electrical Operating Areas

Indoor and outdoor weather protected vehicle cubicles.



SMS FLAME RETARDANT

2 to 36 contacts #16 220V – 13 A HL3/R22 & HL3/R23 - EN45545-2 NFPA 130 compliant





UTS/UT0

3 to 23 contacts #16 110V – 13 A HL2/R22 - HL2/R23 - EN45545-2



SMS IP 3/6 contacts #16 500V – 15 A HL2/R22 - HL3/R23 - EN45545-2



MSG 3U Series

29/41/51 signal contacts 5 Quadrax Low profile I/O connector HL3/R22 & HL3/R23 - EN45545-2 NFPA 130 compliant



SMS IP 3/6/12 contacts #16 500V – 15 A HL3/R22 - HL3/R23 -EN45545-2 500 matings/unmatings



2. Cabin and Interiors

Examples: passenger vehicle compartment and driver cabin.



SMS FLAME RETARDANT

2 to 36 contacts #16 220V – 13 A HL3/R22 & HL3/R23 - EN45545-2 NFPA 130 compliant 500 matings/unmatings



UTO

3 to 48 contacts #16 110V – 13 A HL2/R22 - HL2/R23 - EN45545-2 500 matings/unmatings



UTS LC & MPO





UTS

3 to 23 contacts #16 110V – 13 A HL2/R22 - HL2/R23 - EN45545-2 250 matings/unmatings



VGE1 6 to 60 contacts #20, 16, 12, 8 110V to 500V - 7 to 30A HL3/R22 & HL3/R23 -EN45545-2 NFPA 130 compliant IP66/IP67 Quadrax Ethernet Cat. 6



3. Closed Electrical Operating Areas with Forced Filtered Ventilation

Example: machinery compartment.



SMS IP 3/6 contacts #16

500V - 15 A HL2/R22 - HL3/R23 - EN45545-2



38999

Signal, Power, Quadrax and fiber optic layouts HL3/R22 & HL3/R23 - EN45545-2 5 shell materials



UT0

3 to 48 contacts #16 110V - 13 A HL2/R22 - HL2/R23 - EN45545-2






UTS

3 to 23 contacts #16 110V - 13 A HL2/R22 - HL2/R23 - EN45545-2 250 matings/unmatings



FER1 10/19/37contacts #16 220V - 15 A HL3/R22 & HL3/R23 -FN45545-2 NFPA 130 compliant IP66/IP67 Quadrax Ethernet Cat.6



4. Outdoor Static Applications

Examples: under car body, roof in non weather-protected locations.









VGE1

6 to 60 contacts #20, 16, 12, 8 110V to 500V - 7 to 30 A HL3/R22 & HL3/R23 - EN45545-2 NFPA130 Compliant IP66/IP67 – Quadrax Ethernet Cat.6





VGE1 ELIO® 4/6/8 Fiber optic contacts For multimode fiber HL3/R22 & HL3/R23 - EN45545-2 IP66/IP67

8525

3 to 61 contacts #20 & #16 110V - 13 A HL3/R22 & HL3/R23 - EN45545-2 High contact density 500 matings/unmatings






838

7 to 61 contacts 220V to 500V - 15 to 180 A HL2/R22 & HL3/R23 - EN45545-2 NFPA130 Compliant IP66/IP67 - Quadrax Ethernet Cat.6



838 Elio 8 Elio Contacts HL3/R22 & HL3/R23 -EN45545-2 for multimode fiber Easy to clean IP66/ IP67



5. Outdoor Dynamic Applications

Example: inter-vehicle.



38999

High contact density
Many layouts – 110V
HL3/R22 & HL3/R23 - EN45545-2
IP67 – 5 shell materials





FER1 10/19/37 contacts #16 220V – 15 A HL3/R22 & HL3/R23 - EN45545-2 NFPA 130 compliant IP66/IP67 – Quadrax Ethernet Cat.6





838 QUADRAX


2 to 4 Quadrax 2 to 4 Quadrax HL2/R22 & HL3/R23 - EN45545-2 NFPA 130 compliant IP66/IP67 500h salt spray resistant Ethernet Cat.6






020

7 to 61 contacts 220V to 500V – 15 to 180 A HL2/R22 & HL3/R23 - EN45545-2 NFPA130 Compliant IP66/IP67



VGE1 QUADRAX 1 Quadrax – Ethernet Cat.6 HL3/R22 & HL3/R23 -EN45545-2 IP66/IP67

500h salt spray resistant



6. Outdoor Highly Dynamic Applications

Example: bogie.





VGE1 6 to 60 contacts #20, 16, 12, 8 110V to 500V - 7 to 30 A HL3/R22 & HL3/R23 - EN45545-2 NFPA 130 compliant IP66/IP67





FER1
10/19/37 contacts #16
220V – 15 A
HL3/R22 & HL3/R23 - EN45545-2
NFPA 130 compliant
IP66/IP67
Quadrax Ethernet Cat.6





838 QUADRAX 2 to 4 Quadrax HL2/R22 & HL3/R23 - EN45545-2 NFPA 130 compliant IP66/IP67 500h salt spray resistant Ethernet Cat.6



838
7 to 61 contacts
220V to 500V – 15 to 180 A
HL2/R22 & HL3/R23 - EN45545-2
NFPA 130 compliant
IP66/JP67



VGE1 ELIO® 4/6/8 Fiber optic contacts For multimode fiber HL3/R22 & HL3/R23 EN45545-2 IP66/IP67



7. On-board / On-track Signalling Equipment

Examples: ATC monitoring, sensors, beacons, trackside boxes.









MSG 3U 29/41/51 signal contacts 5 Quadrax Low profile I/O connector HL3/R22 & HL3/R23 - EN45545-2 NFPA 130 compliant





Our Differentiators

EASY

Same contact for 10 connector series Same crimping tools Simplified process

■ HIGH SPEED

Optical Fiber
Quadrax & Cat 6 technologies

ENVIRONMENT AND SAFETY

Compliance to international standards EN50467, EN45545-2, NFPA 130, ROHS, RFACH



SOURIAU: A High Service Level

Worldwide Availability: A Global Network with Local Presence to Serve our Customers



Reliable People, Reliable Solutions

Reliable People, Reliable Solutions



SOURIAU

esterline-connection-technologies.com

MFRAIWSPEN04 © Copyright SOURIAU 2018 - All information in this publication presents only general particulars and shall not form part of any contract. All rights reserved to SOURIAU for changes without prior notification or public announcement. Any duplication is prohibited, unless approved in writing. Cover photography: Ssguy | Shutterstock